

DATASHEET - ZP-ASA/230



Shunt release, 110-415V, 1HP

Part no. ZP-ASA/230
248439
EL Number 1609471
(Norway)

General specifications		
Product name		Eaton Distribution parts
Part no.		ZP-ASA/230
EAN		4015082484392
Product Length/Depth		80 millimetre
Product height		75 millimetre
Product width		26.2 millimetre
Product weight		0.087 kilogram
Compliances		RoHS conform
Certifications		IEC 61373 EN45545-2
Product Tradename		None
Product Type		Distribution parts
Product Sub Type		None
Public Consumption		Yes
PDH Status		Active
Product Family Description		ES-PMCC-PDC-Eaton Distribution parts
Globally Marketable		Yes
Product Specification Details		
Accessory/spare part type		Shunt release
Additional equipment required		Shunt release (for power circuit breaker)
Ambient operating temperature - max		75 °C
Ambient operating temperature - min		-35 °C
Application		Switchgear for industrial and advanced commercial applications
Assembly width		1
Device fitting		Other
EL number		1609471
Functions		Shunt release (for power circuit breaker)
Mounting method		For fitting on left to: FAZ, FRBmM-1N, Z-MS
Number of contacts (change-over contacts)		0
Number of contacts (normally closed contacts)		1
Number of contacts (normally open contacts)		1
Number of poles at main contact unit - max		1
Number of switches (fault signal)		0
Rated operational voltage (Ue) - max		230 V
Rated switch current		0 A
Suitable for current of main contact unit - max		2.1 A
Type		Accessory for miniature circuit breaker Accessory for combined residual current/power circuit breaker Accessory
Used with		Accessory for miniature circuit breaker Accessory Accessory for combined residual current/power circuit breaker Shunt releases
Voltage type		AC

Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)		
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss13-27-14-35-02 [AKE327018])		
Device fitting		Other

Function			Shunt release (for power circuit breaker)
Width in number of modular spacings			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0
Rated switch current		A	0
Rated voltage		V	230
Voltage type			AC
With auto test for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			1
Suitable for max. current main contact unit		A	2.1