

# **PRODUCT FAMILY DATASHEET** PARATHOM CLASSIC A FACILITY

# Professional LED Lamps with added function



## **AREAS OF APPLICATION**

- Wherever light is required quickly
- Hotels, restaurants
- Outdoor applications only in suitable luminaires

- Light also during power outages thanks to backup battery
- Very long lifetime of up to 25,000 h
- Instant 100 % light, no warm-up time
- Variable use at Direct Current, Alternating Current or battery voltage

#### **PRODUCT FEATURES**

- Operating time on battery power: up to 2 h (100 lm)
- Battery charging time: 4 h
- Battery technology: lithium-ion
- Battery charges while the lamp is powered by the mains
- Battery integrated and not interchangeable




## **TECHNICAL DATA**


	Electrical da	ita	Photometrical data						Dimensions & weight	Lifespan
Product description	Nominal wattage	Nominal voltage	Color temper- ature	Lumen main.fact.at end of nom.life time	Light color (designation)	Color temper- ature	Luminous flux	Color render- ing index Ra	Overall length	Nominal lamp life time
P CLAS A 60 8.5 W/2700K E27 <sup>1)</sup>	8.50 W	220240 V	2700 K	0.70	Warm White	2700 K	806 lm	≥80	142.0 mm	25000 h
P CLAS A 75 9.5 W/2700K E27 <sup>1)</sup>	9.50 W	220240 V	2700 K	0.70	Warm White	2700 K	1055 lm	≥80	142.0 mm	25000 h


		Additional product data		Capabilities	Certificates & standards
Product description	Number of switching cycles	Base (standard designation)	Mercury- free	Dimmable	Energy efficiency class
P CLAS A 60 8.5 W/2700K E27 <sup>1)</sup>	100000	E27	Yes	No	A+
P CLAS A 75 9.5 W/2700K E27 <sup>1)</sup>	100000	E27	Yes	No	A+


1) All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

\_\_\_\_









P CLAS A 60 8.5 W/2700K E27

P CLAS A 75 9.5 W/2700K E27

P CLAS A 60 8.5 W/2700K E27

P CLAS A 75 9.5 W/2700K E27

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075125872	Shipping carton box 10	315 mm x 131 mm x 126 mm	1133.00 g	5.20 dm <sup>3</sup>
4058075125896	Shipping carton box 10	315 mm x 131 mm x 126 mm	1133.00 g	5.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.