

PRODUCT DATASHEET

DULUX L LED HF 24 W/3000K 500 mm

OSRAM DULUX L LED HF | LED replacement for CFLni, with 4-pin 2G11 base for ECG and AC mains operation



AREAS OF APPLICATION

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- LED replacement for conventional compact fluorescent lamps for use in ECG luminaires or on AC mains
- Quick, simple and safe replacement
- Simple replacement thanks to similar design as conventional compact fluorescent lamps
- Low energy consumption

PRODUCT FEATURES

- Single-ended four-pin plug-in 2G11 base
- Short and compact pin-base lamp with double-turn tubes
- Type of protection: IP20
- Lifetime: up to 30,000 h
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Rated wattage	24.00 W
Nominal wattage	24.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	50
Max. lamp no. on circuit break. 16 A (B)	80
Operating frequency	50/60 Hz
Inrush current	20.0 A
Power factor λ	> 0.90

Photometrical data

Nominal luminous flux	3000 lm
Rated luminous flux	3000 lm
Rated color temperature	3000 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	3000 K
Luminous flux	3000 lm
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdcn
Color rendering index Ra	≥ 80

Light technical data

Warm-up time (60 %)	< 0.50 s
Beam angle	140 °
Starting time	< 0.5 s

Dimensions & weight



Overall length	535.0 mm
Diameter	44.0 mm
Outer bulb	-
Length	535.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	73 °C

Lifespan

Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	2G11
Mercury content	0.0 mg
Mercury-free	Yes
Show WEEE picto	Yes

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Energy efficiency class	A++
Energy consumption	24 kWh/1000h

Country-specific categorizations

Order reference	DULUX L55LED 24
------------------------	-----------------

SAFETY ADVICE

Only suitable for temperatures of up to 35°C inside of the luminaire.
 Always check the latest update of the compatibility list available on www.ledvance.com/ecg-compatibility
 Not suitable for operation with low-loss and conventional control gears
 Not suitable for tandem operation.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

4058075260887	Folding carton box 1	27 mm x 47 mm x 588 mm	254.00 g	0.75 dm ³
4058075260894	Shipping carton box 10	604 mm x 251 mm x 79 mm	2715.00 g	11.98 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.