


TETRA-18

LED BATTEN LIGHT




Technical Drawing



Technical Data	
Voltage (V)	220-240V
Product Wattage (W)	18
Equivalence with incandescent lamp(W)	144
Colour Render Index (Ra)	>Ra70
Colour Temperature (K)	6400K
Materials	PS + METAL
Protection Class	П
Dimmable	No
EEI	A to A ⁺⁺
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (Im)	1135
Luminous Efficacy (Im/W)	63
Rated Life (hrs)	20.000
IP Rating	20
Power Factor	>0.5
Beam Angle	120°
Size (cm)	60
Number of ON-OFF cycling	x25.000

Product&Family Code: 052 003 0060

Photometric Diagram



C0 Plane beam angle(50%) FC C00 Plane beam angle(50%)
C0 Plane beam angle(50%) 113.7(DEG) C00 Plane beam angle(50%) 124.2(DEG)

Applications

• Designed indoor applications.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base.
- Very low energy consuption.



Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dis Kapi: 2 Ic Kapi: 301 Horozk Electric & Electronic Trade Co. Catalca / Istanbul / Turkey

P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com