


# LED CEILING LAMP






CHROME

### **Technical Drawing**



## Photometric Diagram



Product&Family Code:

036 002 0002



| Technical Data                                     |                      |
|--|----------------------|
| Voltage (V)  | 220-240V             |
| Product Wattage (W)                                | 4                    |
| Equivalence with incandescent<br>lamp(W)           | 32                   |
| Colour Render Index (Ra)                           | >Ra80                |
| Colour Temperature (K)                             | 4000                 |
| Materials  | Aluminium + Glass    |
| Protection Class                                   | 1                    |
| Dimmable   | No                   |
| EEI  | A to A <sup>++</sup> |
| Warm-up time up to 60 %of<br>the full light output | Instant Full Light   |
| Luminous Flux (Im)                                 | 260                  |
| Luminous Efficacy (Im/W)                           | 65                   |
| Rated Life (hrs) 🕒                                 | 30.000               |
| IP Rating  | 20                   |
| Power Factor                                       | >0.5                 |
| Beam Angle   | 120°                 |
| Starting Time                                      | <0.2s                |
| Number of ON-OFF cycling                           | x15.000              |

## Applications

• Styled bedroom, hallway, living room or dining area, all indoor applications.



#### Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- COB LED Lamp Base.
- Very low energy consuption.



P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com