

LED DOWNLIGHT


Product&Family Code: 016 043 1010

SANDRA-10/XL


WHITE

BLACK

Technical Drawing



Technical Data


| | |
|---|--------------------|
| Voltage (V) | 220-240V |
| Product Wattage (W) | 10 |
| Equivalence with incandescent lamp | 80 |
| Colour Render Index (Ra) | >Ra70 |
| Colour Temperature (K) | 4200K |
| Material | Aluminium |
| Protection Class | II |
| Dimmable | No |
| EEI | A to A++ |
| Warm-up time up to 60 %of the full light output | Instant Full Light |
| Luminous Flux (lm) | 700 |
| Luminous Efficacy (lm/W) | 70 |
| Rated Life (hrs) ⌚ | 30.000 |
| IP Rating | 20 |
| Power Factor | >0.5 |
| Beam Angle | 100° |
| Starting Time | <0.2s |
| Number of ON-OFF cycling | x20.000 |

Applications

- Airport, Bathroom, Bedroom, Cinema, Gallery, Hospital, Hotel, Kitchen etc.



Photometric Diagram



C0 Plane beam angle(50%) C90 Plane beam angle(50%)
 C0 Plane beam angle(50%):101.4(DEG) C90 Plane beam angle(50%):100.9(DEG)

Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base.

