

LED DOWNLIGHT




White




Silver

Technical Drawing



Photometric Diagram



Product&Family Code:

016 024 0032



Technical Data	
Voltage (V)	220-240V
Product Wattage (W)	32
Equivalence with incandescent lamp	256
Colour Render Index (Ra)	>Ra80
Colour Temperature (K)	6400K
Materials	Body: Aluminium, Diffuser: Glass
Protection Class	П
Dimmable	No
EEI	A to A ⁺⁺
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (Im)	2400
Luminous Efficacy (Im/W)	75
Rated Life (hrs)	30.000
IP Rating	20
Power Factor	>0.8
Beam Angle	110°
Starting Time	<0.2s
Number of ON-OFF cycling	x25.000

Applications

Airport, Bathroom, Bedroom, Car Park, Cinema, Gallery, Hospital, Hotel, Kitchen, Museum etc.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- Innovative design of assembly structure.
- Extremly Long Life.



Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dıs Kapı: 2 lc Kapı: 301 Horozk Electric & Electronic Trade

P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com