


LED DOWNLIGHT






White

Technical Drawing



Photometric Diagram



Product&Family Code:

016 015 0012

MARIA-12

Technical Data	
Voltage (V)	220-240V
Product Wattage (W)	12
Equivalence with incandescent lamp	96
Colour Render Index (Ra)	>Ra70
Colour Temperature (K)	3000K / 4200K / 6400K
Materials	Aluminium Die Casting Body
Protection Class	II
Dimmable	No
EEI	A to A ⁺⁺
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (Im)	744
Luminous Efficacy (Im/W)	62
Rated Life (hrs) 🕒	30.000
IP Rating	20
Power Factor	>0.5
Beam Angle	120°
Starting Time	<0.2s
Number of ON-OFF cycling	x25.000

Applications

•Airport, Bathroom, Bedroom, Car Park, Cinema, Gallery, Hospital, Hotel, Kitchen, Museum etc.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
 - SMD LED Lamp Base.
 - Aluminum Die Casting Body



Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dıs Kapı: 2 lc Kapı: 301 Horozk Electric & Electronic Trade Co. Catalca / Istanbul / Turkey

P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com