


LED SUSPENSION LIGHT








Technical Drawing



Photometric Diagram



C0 Plane beam angle(50%):109.5(DEG) C90 Plane beam angle(50%):99.1(DEG)

Product&Family Code:

019 009 0085



Technical Data	
Voltage (V)	220-240
Product Wattage (W)	85
Equivalence with incandescent lamp(W)	680
Colour Render Index (Ra)	>Ra80
Colour Temperature (K)	4000K
Materials	Aluminium + Iron + Acrylic
Protection Class	I
Dimmable	No
EEI	A to A++
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (lm)	1400
Luminous Efficacy (Im/W)	17
Rated Life (hrs) 🕒	50.000
IP Rating	20
Power Factor	>0.9
Beam Angle	120°

Applications

• LED Suspension Light has been specifically designed for use indoors and is ideal for both hospitality and residential lighting.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base
- Very low energy consumption



Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dıs Kapı: 2 Ic Kapı: 301 Horozk Electric & Electronic Trad

P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com