


LED SUSPENSION LIGHT




WHITE

Technical Drawing



Photometric Diagram



b C0 Plane beam angle(50%) b C30 Plane beam angle(50%) C0 Plane beam angle(50%):105.3(DEG) C90 Plane beam angle(50%):105.5(DEG)

Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dıs Kapı: 2 lc Kapı: 301 Horozk Electric & Electronic Trad Product&Family Code:

019 003 0042



Technical Data	
Voltage (V)	220-240
Product Wattage (W)	42
Equivalence with incandescent	336
lamp(W)	
Colour Render Index (Ra)	>Ra70
Colour Temperature (K)	4000K
Materials	Metal + Aluminium + Acrylic
Protection Class	1
Dimmable	No
EEI	A to A ⁺⁺
Warm-up time up to 60 %of	Instant Full Light
the full light output	
Luminous Flux (lm)	2940
Luminous Efficacy (Im/W)	70
Rated Life (hrs) 🕒	50.000
IP Rating	10
Power Factor	>0.9
Beam Angle	120°

Applications

• LED Suspension Light has been specifically designed for use indoors and is ideal for both hospitality and residential lighting.



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- SMD LED Lamp Base
- Very low energy consumption



P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com