

PORTO

## LED TRACKLIGHT



125M M

72MM

**Photometric Diagram** 

Colour Render Index (Ra)	>Ra70
Colour Temperature (K)	4200K
Materials	Aluminium
Protection Class	II
Dimmable	No
EEI	A to A <sup>++</sup>
Warm-up time up to 60 %of the full light output	Instant Full Light
Luminous Flux (Im)	525
Luminous Efficacy (Im/W)	75
Rated Life (hrs) 🕒	40.000
IP Rating	20
Power Factor	>0.5
Beam Angle	18° - 70°
Starting Time	<0.2s
Number of ON-OFF cycling	x35.000

100-240V

7

56

## **Applications**

• Tracking lighting is your best choice when compared to other lights for areas such as dining rooms, kitchens, shoping center, jeweler and even offices.





## Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- COB LED Lamp Base.
- Very low energy consuption.



Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dıs Kapı: 2 lc Kapı: 301 Horozk Electric & Electronic Trade

C0 Plane beam angle(50%): 19.6(DEG) C30 Plane beam angle(50%): 19.7(DEG)

CT CO.

Ø41MM

P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com