

LED TRACKLIGHT



Photometric Diagram

150

120

90

MIT: od

00/180

60

-150

-30

-120

-90

60

Product Wattage (W) 23 Equivalence with incandescent 184 lamp(W) Colour Render Index (Ra) >Ra80 Colour Temperature (K) 4200K Materials Aluminium **Protection Class** Ш Dimmable No to A⁺ EEI Warm-up time up to 60 % of Instant Full Light the full light output Luminous Flux (Im) 1550 Luminous Efficacy (Im/W) 67 Rated Life (hrs) 40.000 **IP** Rating 20 **Power Factor** >0.7 24° Beam Angle Starting Time <0.2s

220-240V

Applications

• Tracking lighting is your best choice when compared to other lights for areas such as dining rooms, kitchens, shoping center and even offices.

x20000



Number of ON-OFF cycling



Features

- High Lumen and CRI, Good quality & Constant Current driver.
- High heat dissipation, low carbon and environmental protection.
- COB LED Lamp Base.
- Very low energy consuption.



Istanbul Trakya Free Zone Ferhatpasa S.B. Mah. Acelya Sk. Dıs Kapı: 2 lc Kapı: 301 Horozk Electric & Electronic Trade

AVERAGE BEAM ANGLE (50%) :26.6 DEG

P.+90 (212) 786 62 20 (4 Line) F.+90 (212) 786 62 19 info@horozelektrik.com

Product&Family Code: 018 007 0023

Technical Data

Voltage (V)

PARIS-23