

# PRODUCT DATASHEET

## LEDinestra 40 200° 6 W/2700K S14s

LEDinestra | Tubular LED lamps



---

### AREAS OF APPLICATION

- Ideal for mirror lighting
- Hotels, restaurants
- Domestic applications
- Outdoor applications only in suitable luminaires

---

### PRODUCT BENEFITS

- Long lifetime of up to 15,000 h
- Low energy consumption
- Good color rendering

---

### PRODUCT FEATURES

- LED alternative to tubular incandescent lamps
- Uniform illumination
- Mercury-free lamps
- Bulb made from glass



**TECHNICAL DATA**


Electrical data

<b>Rated wattage</b>	6.00 W
<b>Nominal wattage</b>	6.00 W
<b>Nominal voltage</b>	220...240 V
<b>Max. lamp no. on circuit break. 10 A (B)</b>	300
<b>Max. lamp no. on circuit break. 16 A (B)</b>	500
<b>Operating frequency</b>	50...60 Hz
<b>Inrush current</b>	0.6 A
<b>Claimed equiv. conventional lamp power</b>	40 W

Photometrical data

<b>Rated color temperature</b>	2700 K
<b>Lumen main.fact.at end of nom.life time</b>	0.70
<b>Light color (designation)</b>	Warm White
<b>Color temperature</b>	2700 K
<b>Luminous flux</b>	470 lm
<b>Color rendering index Ra</b>	>80
<b>Nominal luminous flux</b>	470 lm

— **Dimensions & weight**



<b>Overall length</b>	500.0 mm
-----------------------	----------

Temperatures & operating conditions

<b>Maximum temperature at tc test point</b>	50 °C
---	-------

Lifespan

<b>Nominal lamp life time</b>	15000 h
<b>Rated lamp life time</b>	15000 h

<b>Number of switching cycles</b>	100000
-----------------------------------	--------

#### Additional product data

<b>Base (standard designation)</b>	S14s
<b>Mercury-free</b>	Yes

#### Capabilities

<b>Dimmable</b>	No
-----------------	----

#### Certificates & standards

<b>Photobiological safety group EN62778</b>	RG0
<b>Energy efficiency class</b>	A+

#### Country-specific categorizations

<b>ILCOS</b>	DRL/F-6/827-230-S14S-29/500
<b>Order reference</b>	LEDINESTRA40 6W

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075817777	Folding carton box 1	33 mm x 50 mm x 507 mm	167.00 g	0.84 dm <sup>3</sup>
4058075817784	Shipping carton box 10	570 mm x 215 mm x 155 mm	1680.00 g	19.00 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### REFERENCES / LINKS

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.