

Koax-Steckverbinder Coaxial connectors



IEC | Stecker | Compression

IEC | male | compression

- a NITIN-beschichtet (anti-allergen)
- a Montage mit Compression-Werkzeug BWZ 8-00
- a NITIN coated (anti-allergie)
- a To mount with Compression tool BWZ 8-00

premium-line



Artikel Article	CKS 7-48	CKS 7-51
Artikelnummer Part No.	CKS00748	CKS00751
Verpackungseinheit Packing unit	50	
	 EN 50083-2/A1, Klasse A EN 50083-2/A1, class A	
Verwendbar für Koaxialkabel mit Dielektrikumsdurchmesser Suitable for coaxial cable with diameter of dielectricum	4,9 mm SKB 94	5,1 mm SKB 88, 395
Beschreibung Description	axial	



IEC | Kupplung | Compression

IEC | female | compression

- a NITIN-beschichtet (anti-allergen)
- a Montage mit Compression-Werkzeug BWZ 8-00
- a NITIN coated (anti-allergie)
- a To mount with compression tool BWZ 8-00

premium-line



Artikel Article	CKK 7-48	CKK 7-51
Artikelnummer Part No.	CKK00748	CKK00751
Verpackungseinheit Packing unit	50	
	 EN 50083-2/A1, Klasse A EN 50083-2/A1, class A	
Verwendbar für Koaxialkabel mit Dielektrikumsdurchmesser Suitable for coaxial cable with diameter of dielectricum	4,9 mm SKB 94	5,1 mm SKB 88, 395
Beschreibung Description	axial	



F | Stecker | Compression

F | male | compression

- a NITIN-beschichtet (anti-allergen)
- a Montage mit Compression-Werkzeug BWZ 7-00
- a NITIN coated (anti-allergie)
- a To mount with Compression tool BWZ 7-00

premium-line



Artikel Article	CFS 97-48	CFS 97-51
Artikelnummer Part No.	CFS09748	CFS09751
Verpackungseinheit Packing unit	50	
Schirmungsmaß Screening factor	 EN 50083-2/A1, Klasse A EN 50083-2/A1, class A	>100 dB 
Verwendbar für Koaxialkabel mit Dielektrikumsdurchmesser Suitable for coaxial cable with diameter of dielectricum	4,9 mm SKB 94	5,1 mm SKB 88, 395
Schlüsselweite Distance across the flats	11 mm	



F | Stecker | Compression | Quickfix

F | male | compression | Quickfix

premium-line

- a NITIN-beschichtet (antiallergen)
- a Montage mit Compression-Werkzeug BWZ 8-00
- a NITIN coated (anti-allergie)
- a To mount with Compression tool BWZ 8-00



Artikel Article	CFS 99-48	CFS 99-51	CFS 100-48	CFS 100-51
Artikelnummer Part No.	CFS09948	CFS09951	CFS10048	CFS10051
Verpackungseinheit Packing unit	50			
Schirmungsmaß Screening factor	 A EN 50083-2/A1, Klasse A EN 50083-2/A1, class A		>100 dB	 ULTRA HD
Beschreibung Description	axial axial		abgewinkelt right-angled	
Verwendbar für Koaxialkabel mit Dielektrikumsdurchmesser Suitable for coaxial cable with diameter of dielectricum	4,9 mm SKB 94	5,1 mm SKB 88, 395	4,9 mm SKB 94	5,1 mm SKB 88, 395

F | Compression | Sortierboxen

F | compression | connector sets




Artikel Article	BZU 60-00	BZU 60-01	BZU 60-02
Artikelnummer Part No.	BZU06000	BZU06001	BZU06002
Verpackungseinheit Packing unit	1		
Lieferumfang Delivery	leere Box empty box	1 x BWZ 7-00 1 x BWZ 5-01 50 x CFS 97-48 50 x CFS 97-51	1 x BWZ 8-00 1 x BWZ 7-00 1 x BWZ 5-01 50 x CFS 97-48 50 x CFS 97-51 10 x CFS 100-48 10 x CFS 100-51 10 x CFS 99-48 10 x CFS 99-51


F | Stecker | Opti-fix | self compression

F | male | Opti-fix | self compression

premium-line

- a Montage ohne Spezialwerkzeug
- a NITIN-beschichtet (antiallergen)
- a To mount without compression tool
- a NITIN coated (anti-allergie)



Artikel Article	CFS 93-48	CFS 93-51
Artikelnummer Part No.	CFS09348	CFS09351
Verpackungseinheit Packing unit	50	
Schirmungsmaß Screening factor	 A EN 50083-2/A1, Klasse A EN 50083-2/A1, class A	
Verwendbar für Koaxialkabel mit Dielektrikumsdurchmesser Suitable for coaxial cable with diameter of dielectricum	4,9 mm SKB 94	5,1 mm SKB 88, 395
Schlüsselweite Distance across the flats	11 mm	