

DATA SHEET: DSRT-DOORS FOR DATAENCLOSURES DS AND DSZ













APPLICATION

All Doors are constructed for installation to SCHRACK free-standing Data-enclosures DS and DSZ. Doors can be installed in front as a replacement of the standard glass-door or in the rear instead of the rear-panel. Installation of door in the rear enables easier and quicker access to the backside of installed components for repair, maintenance or exchange.

Glassdoors to be used if it is necessary to look at installed components.

Solid Metaldoors if no view inside the cabinet shall be possible, e.g. in public areas.

Perforated Metaldoors for enhanced passive cooling of the installed active equipment..

Double-wing doors are used in case of limited space for opening of doors.

SCHRACK TECHNIK GMBH PAGE 1/2

■ TECHNICAL DATA

- Material:
 - Steel
 - Door glass: safety hardened, thickness 4 mm
- Color: Lightgrey RAL 7035
- IP protection: IP 30
- Comfort swinghandle preparred for halfcylinder-lock.
- Installation:
 - Front: Instead of standard glas-door
 - Rear: Instead of standard fullmetal rear-panel
- Hinges: 3 pcs. at 42U and 45U doors, opening angle: 170 degrees
- Hinging: Right. Quick and easy changing to hinging left.
- Supply includes all materials needed for installation in front or rear.

DESCRIPTION	ORDER NUMBER
Door for dataenclosure DS and DSZ, 42U, 600 wide, Perforated	DSRT4261
Door for dataenclosure DS and DSZ, 42U, 600 wide, Solid Metal	DSRT4262
Door for dataenclosure DS and DSZ, 42U, 600 wide, Glasdoor	DSRT4263
Double-wing-door for dataenclosure DS and DSZ, 42U, 600 wide, Perforated	DSRT4265
Double-wing-door for dataenclosure DS and DSZ, 42U, 600 wide, Solid Metal	DSRT4266
Double-wing-door for dataenclosure DS and DSZ, 42U, 600 wide, Glasdoor	DSRT4267
Door for dataenclosure DS and DSZ, 42U, 800 wide, Perforated	DSRT4281
Door for dataenclosure DS and DSZ, 42U, 800 wide, Solid Metal	DSRT4282
Door for dataenclosure DS and DSZ, 42U, 800 wide, Glasdoor	DSRT4283
Double-wing-door for dataenclosure DS and DSZ, 42U, 800 wide, Perforated	DSRT4285
Double-wing-door for dataenclosure DS and DSZ, 42U, 800 wide, Solid Metal	DSRT4286
Double-wing-door for dataenclosure DS and DSZ, 42U, 800 wide, Glasdoor	DSRT4287
Door for dataenclosure DS and DSZ, 45U, 600 wide, Perforated	DSRT4561
Door for dataenclosure DS and DSZ, 45U, 600 wide, Solid Metal	DSRT4562
Door for dataenclosure DS and DSZ, 45U, 600 wide, Glasdoor	DSRT4563
Double-wing-door for dataenclosure DS and DSZ, 45U, 600 wide, Perforated	DSRT4565
Double-wing-door for dataenclosure DS and DSZ, 45U, 600 wide, Solid Metal	DSRT4566
Double-wing-door for dataenclosure DS and DSZ, 45U, 600 wide, Glasdoor	DSRT4567
Door for dataenclosure DS and DSZ, 45U, 800 wide, Perforated	DSRT4581
Door for dataenclosure DS and DSZ, 45U, 800 wide, Solid Metal	DSRT4582
Door for dataenclosure DS and DSZ, 45U, 800 wide, Glasdoor	DSRT4583
Double-wing-door for dataenclosure DS and DSZ, 45U, 800 wide, Perforated	DSRT4585
Double-wing-door for dataenclosure DS and DSZ, 45U, 800 wide, Solid Metal	DSRT4586
Double-wing-door for dataenclosure DS and DSZ, 45U, 800 wide, Glasdoor	DSRT4587

SCHRACK TECHNIK GMBH

PAGE 2/2