







# 1.25

## SUPRA



**APLICACIONES INDICADAS** / SUITABLE APPLICATIONS / APPLICATIONS APPROPRIÉES



IT - DE



IP65



EN 60598-1




**TUBO FLUORESCENTE / LAMP / LAMPE**


T8

Ref. Acrylic Acrylic Acrylique	Ref. PC	Potencia Watts Puissance (W)	Equipo Equipment Ballast ■	A (mm)	B (mm)	C (mm)	D (mm)	Cierres Fasteners Fermetures	Embalaje Packaging Emballage
S0107	S1107	1 x 18	■	664	260	100	110	6	1
S0108	S1108	1 x 36	■	1.274	870	100	110	8	1
S0109	S1109	1 x 58	■	1.575	650	100	110	12	1
S0119	S1119	2 x 18	■	664	260	160	110	6	1
S0120	S1120	2 x 36	■	1.274	650	160	110	8	1
S0121	S1121	2 x 58	■	1.575	650	160	110	12	1

■ **Electrónica / Electronic / Électronique**



1x



2x

# 1.25


## SUPRA

### TUBO FLUORESCENTE / LAMP / LAMPE


T5

Ref. Acrylic Acrylique	Ref. PC	Potencia Watts Puissance (W)	Equipo Equipment Ballast	A (mm)	B (mm)	C (mm)	D (mm)	Cierres Fasteners Fermetures	Embalaje Packaging Emballage
S2001	S2101	1 x 14	■	664	260	100	110	6	1
S2004	S2104	1 x 24	■	664	260	100	110	6	1
S2002	S2102	1 x 28	■	1.274	870	100	110	8	1
S2003	S2103	1 x 35	■	1.575	650	100	110	12	1
S2005	S2105	1 x 49	■	1.575	650	100	110	12	1
S2006	S2106	1 x 54	■	1.274	870	100	110	8	1
S2007	S2107	1 x 80	■	1.575	650	100	110	12	1
S2008	S2108	2 x 14	■	664	260	100	110	6	1
S2011	S2111	2 x 24	■	664	260	100	110	6	1
S2009	S2109	2 x 28	■	1.274	870	100	110	8	1
S2010	S2110	2 x 35	■	1.575	650	100	110	12	1
S2012	S2112	2 x 49	■	1.575	650	160	110	12	1
S2013	S2113	2 x 54	■	1.274	870	160	110	8	1

■ Electrónica / Electronic / Électronique



1x



2x

IP65

CE

**REFLECTOR ALUMINIO BRILLANTE**  
GLOSSY ALUMINIUM REFLECTOR  
RÉFLECTEUR ALUMINIUM BRILLANT

Potencia Watts (W) Puissance	1 x 14/24	1 x 28/54	1 x 35/49/80	2 x 14/24	2 x 28/54	2 x 35/49
------------------------------------	-----------	-----------	--------------	-----------	-----------	-----------

**TUBO LED / LED TUBE / TUBE LED**


Ref. Acrylic Acrylique	Ref. PC	Longitud Tubo Tube Length Longueur Tube	A	B	C	D	Embalaje Packaging Emballage
		(mm)	(mm)	(mm)	(mm)	(mm)	
S0107L	S1107L	1 x 600	664	260	100	110	1
S0108L	S1108L	1 x 1.200	1.274	870	100	110	1
S0109L	S1109L	1 x 1.500	1.575	650	100	110	1
S0119L	S1119L	2 x 600	664	260	160	110	1
S0120L	S1120L	2 x 1.200	1.274	650	160	110	1
S0121L	S1121L	2 x 1.500	1.575	650	160	110	1

**ACCESORIOS SUPRA / SUPRA ACCESORIES / ACCESSOIRES SUPRA**































































Ref.	S2150	S2151
	<b>Grapa de acero inoxidable</b> Stainless steel clip Clip acier inox	<b>Sujeción a carril DELTA</b> Delta rail fastening Platine de fixation sur rail DELTA

<b>LÍNEA CONTINUA</b> CONTINUOUS LINE CONNECTION CÂBLAGE TRAVERSANT	<b>3 polos / 3 poles / 3 pôles</b>	<b>Ref. S0122</b>
	<b>5 polos / 5 poles / 5 pôles</b>	<b>Ref. S0123</b>



**EMERGENCY**  
1h / 3h

	Cuerpo luminaria tubo policarbonato Polycarbonate luminaire body Corps du luminaire tube polycarbonate		Cuerpo extrusion Aluminum body Corps aluminium		Rango de temperaturas Temperatures range Tranche de temperatures
	Cuerpo luminaria metacrilato Methacrylate luminaire body Corps du luminaire méthacrylate		Cuerpo Acero Prelacado Pre-lacquered steel body Corps en acier prélaqué		Ensayo hilo Glow wire test Essais fil incandescent
	Cuerpo luminaria vidrio borosilicato Glass borosilicate luminaire body Corps du luminaire verre borosilicate		Cuerpo Aluminio Prelacado Pre-lacquered aluminum body Corps en aluminium prélaqué		Alto factor High Factor Hautes temperatures
	Cuerpo luminaria ABS ABS luminaire body Corps du luminaire ABS		Cuerpo ABS ABS body Corp ABS		Conector rápido Quick Connector Connecteur rapide
	Cuerpo luminaria poliestireno Polystyrene luminaire body Corps du luminaire polystyrène		Difusor Policarbonato Polycarbonate Diffuser Diffuseur Polycarbonate		Entrada cablesosca M25 (2e) M25 Cable entry (2e) Entrée de câbles a vis M25 (2e)
	Cuerpo aluminio Extrusion Aluminum Body Corps extrusion aluminium		Difusor Policarbonato Opal Opal Polycarbonate Diffuser Diffuseur Polycarbonate Opal		Regulación de flujo Dimmable equipment Ballast gradable
	Cuerpo hierro Iron body Corps fer		Difusor Poliestireno Polystyrene Diffuser Diffuseur Polystyrène		Módulo LED LED Module Modules LED
	Tapas Aluminio pintado Painted Aluminum end caps Embouts aluminium peint		Difusor PC/ACRIL PC/ACRIL Diffuser Diffuseur PC/ACRIL		Tubo LED LED Tube Tube LED
	Tapa acero INOX Stainless Steel 304 end caps Embouts INOX 304		Lamas ABS ABS louvers Lames ABS		Tubo fluorescencia Fluorescent Tube Tube Fluorescent
	Tapa acero INOX Stainless Steel 316 end caps		Lamas ABS - PC ABS - PC Louvers Lames ABS - PC		Tubo LED o Tubo fluorescente LED Tube or fluorescent tube Tube LED ou Tube fluorescent
	Tapas ABS ABS Plastic end caps Embouts PLASTIQUE ABS		Abrazaderas acero cincado Galvanized Steel Clamps Fixations acier zingué		Fuente de luz Light source Source de lumière
	Tapas Policarbonato PC Plastic end caps Embouts PLASTIQUE PC		Brazaderas acero inox Stainless Steel Clamps Fixations INOX		Fuente de luz Light source Source de lumière
	Tapas Plástico Metalizado Metalized Plastic end caps Embouts PLASTIQUE CHROMÉ		Abrazaderas cierre rápido Quick opening stainless steel Fixations INOX ouverture à grenouillère		Fuente de luz Light source Source de lumière
	Tapas Zamak Niquelado Nickel-plated ZAMAK end caps Embouts ZAMAK NICKELÉ		Abrazaderas PC antivandálica Vandalism PC Clamps Fixations INOX ouverture à grenouillère		Zona ATEX EX Area ATEX Zone
	Tapas acero niquelado Nickel-plated steel end caps Embouts Acier Nickelé		Abrazaderas ABS ABS Clamps Fixations PMMA antivandalismo		Sistema de emergencia Emergency Sistem Système d'urgence
	Aluminio Anodizado Anodized aluminum Aluminium anodisé		Aro ABS ABS Ring Fixations ABS		Grupo de riesgo fotobiológico Photobiological risk group Group de risque photobiologique
	Reflector Aluminio brillo Reflector Aluminum Gloss Réflecteur Aluminium brillant		Abrazaderas techo o pared Ceiling or wall Clamps Fixations murs et parois		Índice MacAdam MacAdam Ellipse Taux MacAdam
	Reflector chapa lacada blanca White lacquered steel Reflector Réflecteur tôle lacquée blanc		Prensaestopa Cable Gland Presse étoupes		Índice de deslumbramiento unificado Unify glade rating Taux d'éblouissement
	Reflector acero lacado blanco White Lacquered Steel Reflector Réflecteur acier lacqué blanc		Empotrable para lámpara Embedded for lamps Encastrable pour lamp		Índice cromático Chromatic Index Taux chromatique
	Reflector acero galvanizado Galvanized Steel Reflector Réflecteur acier galvanisé		Brida suspensión perforación 18mm Clamps suspension borehole 18 mm Fixation avec suspension perforation 18 mm		Vida útil Useful life Durée de vie