



Cumpara

APC
[G55TBATCABH](#)

Prezentare generală

Descriere	Matching battery cabinet for extended runtime options. Cabinet includes batteries, Cabling for side by side configuration, DC breaker and temperature sensor.
Denumire model	MGE Galaxy 5500 Backup Time 400V
Include	Installation guide , User Manual
Timp de livrare standard	Usually Ships within 2 Weeks
Distribuire produs	Andorra , United Arab Emirates , Albania , Armenia , Angola , Austria , Azerbaijan , Bosnia And Herzegovina , Bangladesh , Belgium , Burkina Faso , Bulgaria , Bahrain , Burundi , Benin , Botswana , Belarus , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Central African Republic , Congo , Switzerland , Cote D'Ivoire , Cameroon , Serbia And Montenegro , Cyprus , Czech Republic , Germany , Djibouti , Denmark , Algeria , Estonia , Egypt , Western Sahara , Spain , Ethiopia , Finland , France , Gabon , United Kingdom , Georgia , French Guiana , Ghana , Gibraltar , Gambia , Guinea , Guadeloupe , Equatorial Guinea , Greece , Croatia , Hungary , Ireland , Israel , India , Iraq , Iran (Islamic Republic Of) , Iceland , Italy , Jordan , Kenya , Kuwait , Kazakhstan , Lebanon , Liechtenstein , Sri Lanka , Liberia , Lesotho , Lithuania , Luxembourg , Latvia , Morocco , Moldova , Republic Of , Madagascar , Macedonia , Mali , Martinique , Mauritania , Malta , Mauritius , Malawi , Mozambique , Namibia , Niger , Nigeria , Netherlands , Norway , Oman , Pakistan , Poland , Portugal , Reunion , Romania , Russian Federation , Rwanda , Saudi Arabia , Sudan , Sweden , Slovenia , Slovakia (Slovak Republic) , Sierra Leone , Senegal , Somalia , Turks And Caicos Islands , Chad , Togo , Turkmenistan , Tunisia , Turkey , TANZANIA, UNITED REPUBLIC OF , Ukraine , Uganda , Uzbekistan , Yemen , Mayotte , South Africa , Zambia , Zimbabwe

Durată de funcționare baterii &

Tip de acumulator	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Montare baterie	Enclosed battery cabinet
Montare baterie	8 - 10
Amplasare baterie	Battery Cabinet

Caracteristici fizice

Greutate netă	230 kg
---------------	--------

Înălțime maximă	1900 mm
Lățime maximă	711 mm
Adâncime maximă	820 mm
Greutate de transport	250 kg
Lățime de transport	762 mm
Înălțime transport	1930 mm
Adâncime transport	838 mm
Culoare	Grey
Unități per palet	1.0

Ambiental

Mediu de operare	0 - 40 °C
Umiditate relativă de funcționare	5 - 90 %
Înălțime de operare	0-999.9 meters
Temperatură de depozitare	-20 - 45 °C
Umiditate relativă depozitare	5 - 90 %
Înălțime depozitare	0-9000 meters

Conformanță

Aprobări reglementare	ISO 14001 , ISO 9001 , TUV
Garanție standard	1 year repair or replace