


USER MANUAL / KULLANMA KILAVUZU
BEDIENUNGSANLEITUNG / ПАСПОРТ ИЗДЕЛИЯ




SMD LED Floodlight

- EN Mounting instructions
- FR Instruction de montage
- GR Συναρμολογησης
- RS Uputstvo za montažu
- DE Montageanleitung
- TR Montaj talimatı
- RO Instrucțiunile de montaj
- UA Інструкція по монтажу
- RU Инструкция по монтажу
- ESP Instrucciones de montaje
- BG Ръководство за монтаж
- AR تعليمات التثبيت


MODEL NO	INPUT VOLTAGE (VAC)	POWER (W) ±10%	LUMEN (Lm) ±10%	WORK TEMPERATURE (°C)	IP	WORK HUMIDITY (RH)	CCT	CRI
BT61-01002	220-240	10	800	-20°C/+40°C	IP65	5%-95%	3000K	>80
BT61-01012	220-240	10	800	-20°C/+40°C	IP65	5%-95%	4200K	>80
BT61-01032	220-240	10	800	-20°C/+40°C	IP65	5%-95%	6500K	>80
BT61-02002	220-240	20	1600	-20°C/+40°C	IP65	5%-95%	3000K	>80
BT61-02012	220-240	20	1600	-20°C/+40°C	IP65	5%-95%	4200K	>80
BT61-02032	220-240	20	1600	-20°C/+40°C	IP65	5%-95%	6500K	>80
BT61-03002	220-240	30	2400	-20°C/+40°C	IP65	5%-95%	3000K	>80
BT61-03012	220-240	30	2400	-20°C/+40°C	IP65	5%-95%	4200K	>80
BT61-03032	220-240	30	2400	-20°C/+40°C	IP65	5%-95%	6500K	>80
BT61-05002	220-240	50	4000	-20°C/+40°C	IP65	5%-95%	3000K	>80
BT61-05012	220-240	50	4000	-20°C/+40°C	IP65	5%-95%	4200K	>80
BT61-05032	220-240	50	4000	-20°C/+40°C	IP65	5%-95%	6500K	>80
BT61-07002	220-240	70	5600	-20°C/+40°C	IP65	5%-95%	3000K	>80
BT61-07012	220-240	70	5600	-20°C/+40°C	IP65	5%-95%	4200K	>80
BT61-07032	220-240	70	5600	-20°C/+40°C	IP65	5%-95%	6500K	>80
BT61-09102	220-240	100	8000	-20°C/+40°C	IP65	5%-95%	3000K	>70
BT61-09112	220-240	100	8000	-20°C/+40°C	IP65	5%-95%	4200K	>70
BT61-09132	220-240	100	8000	-20°C/+40°C	IP65	5%-95%	6500K	>70
BT61-09402	220-240	150	12000	-20°C/+40°C	IP65	5%-95%	3000K	>70
BT61-09412	220-240	150	12000	-20°C/+40°C	IP65	5%-95%	4200K	>70
BT61-09432	220-240	150	12000	-20°C/+40°C	IP65	5%-95%	6500K	>70
BT61-09602	220-240	200	16000	-20°C/+40°C	IP65	5%-95%	3000K	>70
BT61-09612	220-240	200	16000	-20°C/+40°C	IP65	5%-95%	4200K	>70
BT61-09632	220-240	200	16000	-20°C/+40°C	IP65	5%-95%	6500K	>70
BT61-23002	220-240	30	2400	-20°C/+40°C	IP44	5%-95%	3000K	>80
BT61-23012	220-240	30	2400	-20°C/+40°C	IP44	5%-95%	4200K	>80
BT61-23032	220-240	30	2400	-20°C/+40°C	IP44	5%-95%	6500K	>80




10W
BT61-01002
BT61-01012
BT61-01032




20W
BT61-02002
BT61-02012
BT61-02032




30W
BT61-03002
BT61-03012
BT61-03032




50W
BT61-05002
BT61-05012
BT61-05032




70W/100W
BT61-07002/BT61-09102
BT61-07012/BT61-09112
BT61-07032/BT61-09132



150W
BT61-09402
BT61-09412
BT61-09432



200W
BT61-09602
BT61-09612
BT61-09632



30W-sensor
BT61-23002
BT61-23012
BT61-23032

Manufacturer:
DEMGRUP INTERNATIONAL CO., LTD
Chengxing Road, No. 89, Hangzhou, China
www.demgroup.com.tr

Produced For:
Braytron S.R.L
Bulevardul Iuliu Maniu, Nr.616, Sector 6,
061129 Bucharest - Romania
info@braytron.com www.braytron.com

Importer(Turkey):
Spot Elektrik Aydınlatma Ve Mum. San. Tic. Ltd.Sti.
Eksioglu Mah. Saray Cad. No.7-9
34794 - Cekmekoy Istanbul - Turkey
www.braytron.com

Importer(Romania):
S.C. Spotvision Electric Lighting S.R.L
Bulevardul Iuliu Maniu, Nr.616, Sector 6,061129
Bucharest - Romania
www.spotvisionelectric.ro



