

xeon

3 YEARS
WARRANTY



EN

Round or square ceiling light fittings, with flat shape, equipped with SMD LEDs modules.

Housing of steel sheet, electrostatically painted.

Diffuser of opal acryl.

Rotating clamps for fixing in polycarbonate.

LED modules with lenses with very wide dispersion, to ensure good diffusion and uniformity of light.

Constant current LED driver delivered with the ceiling light fitting.

Block of terminals 2P+N (10A/250V/2,5mm²).

Range of Applications

General interior lighting.

RO

Plafoniere rotunde sau pătrate, cu formă plată, echipate cu module cu LED-uri SMD.

Carcasă din tablă de oțel, vopsită în câmp electrostatic.

Dispersor din acril opal.

Cleme de fixare pivotante din policarbonat.

Module cu LED-uri având lentile cu dispersie foarte largă, care asigură o difuzie și uniformitate foarte bune ale iluminatului.

Alimentator în curent constant livrat împreună cu plafoniera.

Clemă de conexiuni 2P+N (10A/250V/2,5mm²).

Aplicații

Iluminatul general de interior.

IT

Plafoniere rotonde o quadrate, forma piatta, equipaggiate con moduli a LED SMD.

Carcassa in lamiera d'acciaio, verniciata a polveri.

Diffusore in acrilico opale.

Ganci rotanti in policarbonato per una rapida installazione.

Moduli LED con lenti grandangolari che garantiscono una ampia diffusione e uniformità di illuminazione.

Alimentatore in corrente costante fornito con plafoniera.

Morsettiera 2P+N (10A/250V/2,5mm²).

Campi di applicazione

Iluminazione generale per interni.




EN01

EN02

EN03

FINISHING AVAILABLE

WH



Code	Finishing	Type of LED	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
EN01WW	WH	SMD 2835 SAN'AN	24W	180-250V AC	Included	2400 lm	1683 lm	3000K	80	160°	1.55 kg
EN01NW	WH	SMD 2835 SAN'AN	24W	180-250V AC	Included	2520 lm	1814 lm	4000K	80	160°	1.55 kg
● EN01CW	WH	SMD 2835 SAN'AN	24W	180-250V AC	Included	2550 lm	1831 lm	6000K	80	160°	1.55 kg
EN02WW	WH	SMD 2835 SAN'AN	36W	180-250V AC	Included	3300 lm	2508 lm	3000K	80	160°	1.95 kg
EN02NW	WH	SMD 2835 SAN'AN	36W	180-250V AC	Included	3465 lm	2702 lm	4000K	80	160°	1.95 kg
● EN02CW	WH	SMD 2835 SAN'AN	36W	180-250V AC	Included	3510 lm	2729 lm	6000K	80	160°	1.95 kg
EN03WW	WH	SMD 2835 SAN'AN	56W	180-250V AC	Included	5600 lm	3892 lm	3000K	80	160°	2.15 kg
EN03NW	WH	SMD 2835 SAN'AN	56W	180-250V AC	Included	5880 lm	4203 lm	4000K	80	160°	2.15 kg
● EN03CW	WH	SMD 2835 SAN'AN	56W	180-250V AC	Included	5895 lm	4243 lm	6000K	80	160°	2.15 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

EN04





EN05

EN06

EN07

FINISHING AVAILABLE

WH



Code	Finishing	Type of LED	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
EN04WW	WH	SMD 2835 SAN'AN	24W	180-250V AC	Included	2400 lm	1723 lm	3000K	80	160°	1.60 kg
EN04NW	WH	SMD 2835 SAN'AN	24W	180-250V AC	Included	2520 lm	1847 lm	4000K	80	160°	1.60 kg
● EN04CW	WH	SMD 2835 SAN'AN	24W	180-250V AC	Included	2550 lm	1865 lm	6000K	80	160°	1.60 kg
EN05WW	WH	SMD 2835 SAN'AN	36W	180-250V AC	Included	3600 lm	2596 lm	3000K	80	160°	2.05 kg
EN05NW	WH	SMD 2835 SAN'AN	36W	180-250V AC	Included	3780 lm	2774 lm	4000K	80	160°	2.05 kg
● EN05CW	WH	SMD 2835 SAN'AN	36W	180-250V AC	Included	3825 lm	2798 lm	6000K	80	160°	2.05 kg
EN06WW	WH	SMD 2835 SAN'AN	56W	180-250V AC	Included	5600 lm	3985 lm	3000K	80	160°	2.30 kg
EN06NW	WH	SMD 2835 SAN'AN	56W	180-250V AC	Included	5880 lm	4287 lm	4000K	80	160°	2.30 kg
● EN06CW	WH	SMD 2835 SAN'AN	56W	180-250V AC	Included	5895 lm	4296 lm	6000K	80	160°	2.30 kg
EN07WW	WH	SMD 2835 SAN'AN	76W	180-250V AC	Included	8000 lm	5327 lm	3000K	80	160°	3.00 kg
EN07NW	WH	SMD 2835 SAN'AN	76W	180-250V AC	Included	8400 lm	5753 lm	4000K	80	160°	3.00 kg
● EN07CW	WH	SMD 2835 SAN'AN	76W	180-250V AC	Included	8500 lm	5787 lm	6000K	80	160°	3.00 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

