


xform square

5 YEARS WARRANTY



EN
Surface (on the wall or on the ceiling) light fittings equipped with SMD LED, square shape.
Long lasting, low power consumption and high lumen output.
Die-cast aluminum housing, electrostatically painted.
Clamping device made of steel sheet.
Diffuser of polystyrene, with screen printing grid and polyethylene reflector.
Constant current LED driver delivered with the panel.
Connector "plug-in" type between LED panel and driver.
Connector 2P, 2,5mm² max. at the driver entry.
Range of applications
General interior lighting.

RO
Corpuri de iluminat echipate cu LED-uri SMD, cu formă pătrată, pentru montaj aparent pe perete sau tavan.
Durată mare de viață, consum redus de energie și flux luminos mare.
Corp din aluminiu turnat sub presiune, vopsit în câmp electrostatic.
Bridă de fixare din tablă de oțel.
Dispersor din polistiren cu rețea de difuzie serigrafată și reflector din polietilenă.
Alimentator în curent constant livrat împreună cu panoul.
Conector tip "plug-in" între panou și alimentator.
Conector 2P, max. 2,5mm² la intrarea în alimentator.
Aplicații
Iluminat general de interior.

IT
Apparecchi a LED SMD, forma quadrata, per montaggio a parete o a soffitto.
Garantiscono una maggiore vita operativa, risparmio energetico ed alta resa luminosa.
Corpo in pressofusione di alluminio, verniciato a polveri.
Staffa di fissaggio in lamiera di acciaio.
Diffusore in polistirene, con retino diffusore serigrafato e riflettore in polietilene.
Alimentatore in corrente costante fornito con il pannello.
Connettore tipo "plug-in" tra pannello e l'alimentatore.
Connettore 2P, max. 2,5mm² all'entrata dell'alimentatore.
Campi di applicazione
Illuminazione generale d'interni.





FMQ168

FMQ220

FMQ300

FINISHING AVAILABLE

MWH



Code	Finishing	Type of LED	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
FMQ168WW MWH	MWH	SMD 2016 EPISTAR	15W	220-240V AC	Included	1450 lm	909 lm	3000K	83	110°	0.86 kg
FMQ168NW MWH	MWH	SMD 2016 EPISTAR	15W	220-240V AC	Included	1560 lm	968 lm	4000K	82	110°	0.86 kg
● FMQ168CW MWH	MWH	SMD 2016 EPISTAR	15W	220-240V AC	Included	1585 lm	984 lm	6000K	80	110°	0.86 kg
FMQ220WW MWH	MWH	SMD 2016 EPISTAR	22W	220-240V AC	Included	2120 lm	1521 lm	3000K	83	110°	1.25 kg
FMQ220NW MWH	MWH	SMD 2016 EPISTAR	22W	220-240V AC	Included	2280 lm	1627 lm	4000K	82	110°	1.25 kg
● FMQ220CW MWH	MWH	SMD 2016 EPISTAR	22W	220-240V AC	Included	2320 lm	1656 lm	6000K	80	110°	1.25 kg
FMQ300WW MWH	MWH	SMD 2016 EPISTAR	30W	220-240V AC	Included	2900 lm	1992 lm	3000K	83	110°	1.97 kg
FMQ300NW MWH	MWH	SMD 2016 EPISTAR	30W	220-240V AC	Included	3120 lm	2131 lm	4000K	82	110°	1.97 kg
● FMQ300CW MWH	MWH	SMD 2016 EPISTAR	30W	220-240V AC	Included	3170 lm	2174 lm	6000K	80	110°	1.97 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE