


xcore

3 YEARS
WARRANTY



EN

Round or square ceiling light fittings for interior, surface mounted, equipped with COB LEDs. Structure of die-cast aluminum, electrostatically painted.

Optical system with FRESNEL lens of polycarbonate, UGR<10.

Constant current LED driver included.

Range of applications

General interior lighting, decorative lighting.

RO

Plafoniere rotunde sau pătrate, de interior, pentru montaj aparent, echipate cu LED-uri COB.

Structură din aluminiu turnat, vopsită în câmp electrostatic.

Sistem optic cu lentilă FRESNEL din policarbonat. Alimentator LED în curent constant inclus, UGR<10.

Aplicații

Iluminatul general de interior, iluminatul decorativ.

IT

Plafoniere tonde o quadrate per interni, montaggio da superficie, equipaggiate con LED COB.

Struttura in pressofusione di alluminio, verniciato a polveri.

Sistema ottico con lente FRESNEL in policarbonato, UGR<10.

Alimentatore LED in corrente costante incluso.


Campi di applicazione

Illuminazione generale d'interni, illuminazione decorativa.

XCORE ROUND

FINISHING AVAILABLE

MWH MBK



CRR01

CRR02




Code	Finishing	Type of LED	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
CRR01WW MWH	MWH	COB CREE	6W	220-240V AC	Included	780 lm	482 lm	3000K	80	38°	0.25 kg
CRR01NW MWH	MWH	COB CREE	6W	220-240V AC	Included	840 lm	514 lm	4000K	80	38°	0.25 kg
CRR01WW MBK	MBK	COB CREE	6W	220-240V AC	Included	780 lm	482 lm	3000K	80	38°	0.25 kg
CRR01NW MBK	MBK	COB CREE	6W	220-240V AC	Included	840 lm	514 lm	4000K	80	38°	0.25 kg
CRR02WW MWH	MWH	COB CREE	18W	220-240V AC	Included	2100 lm	1397 lm	3000K	80	38°	0.52 kg
CRR02NW MWH	MWH	COB CREE	18W	220-240V AC	Included	2260 lm	1489 lm	4000K	80	38°	0.52 kg
CRR02WW MBK	MBK	COB CREE	18W	220-240V AC	Included	2100 lm	1397 lm	3000K	80	38°	0.52 kg
CRR02NW MBK	MBK	COB CREE	18W	220-240V AC	Included	2260 lm	1489 lm	4000K	80	38°	0.52 kg

XCORE SQUARE

FINISHING AVAILABLE

MWH MBK



CRQ01

CRQ02



Code	Finishing	Type of LED	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
CRQ01WW MWH	MWH	COB CREE	6W	220-240V AC	Included	780 lm	479 lm	3000K	80	38°	0.19 kg
CRQ01NW MWH	MWH	COB CREE	6W	220-240V AC	Included	840 lm	512 lm	4000K	80	38°	0.19 kg
CRQ01WW MBK	MBK	COB CREE	6W	220-240V AC	Included	780 lm	479 lm	3000K	80	38°	0.19 kg
CRQ01NW MBK	MBK	COB CREE	6W	220-240V AC	Included	840 lm	512 lm	4000K	80	38°	0.19 kg
CRQ02WW MWH	MWH	COB CREE	18W	220-240V AC	Included	2100 lm	1395 lm	3000K	80	38°	0.56 kg
CRQ02NW MWH	MWH	COB CREE	18W	220-240V AC	Included	2260 lm	1487 lm	4000K	80	38°	0.56 kg
CRQ02WW MBK	MBK	COB CREE	18W	220-240V AC	Included	2100 lm	1395 lm	3000K	80	38°	0.56 kg
CRQ02NW MBK	MBK	COB CREE	18W	220-240V AC	Included	2260 lm	1487 lm	4000K	80	38°	0.56 kg