


XVOSS

**3 YEARS
WARRANTY**



EN

Series of ceiling luminaires for interior, surface mounted, equipped with SMD LEDs.

Structure of die-cast aluminum, electrostatically painted.

The element for mounting of steel sheet.

The light fittings are equipped with opal polycarbonate diffusers.

Constant current LED driver included.

Block of terminals 2P+N (10A/250V/2,5mm²).

Range of applications

General interior lighting, decorative lighting.

RO

Serie de plafoniere pentru interior, cu montaj aparent, echipate cu LED-uri SMD.

Structură din aluminiu turnat, vopsită în câmp electrostatic.

Element de montaj din tablă de oțel.

Corpurile de iluminat sunt prevăzute cu dispersoare opale din policarbonat.

Alimentator LED în curent constant inclus.

Clemă de conexiuni 2P+N (10A/250V/2,5mm²).

Aplicații

Iluminatul general de interior, iluminatul decorativ.

IT

Serie di plafoniere per interno, montaggio da superficie, dotate di LED SMD.

Struttura in pressofusione di alluminio, verniciato a polveri.

Elemento di montaggio in lamiera di acciaio.

Gli apparecchi sono dotati di diffusori opalini in policarbonato.

Alimentatore LED in corrente costante incluso.

Morsetteria 2P+N (10A/250V/2,5mm²).




Campi di applicazione

Illuminazione generale d'interni, illuminazione decorativa.

VS01

FINISHING AVAILABLE

MWH **MBK**



Code	Finishing	Type of LED	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CR1	Optics	Weight
VS01WW MWH	MWH	SMD 3030 OSRAM	10W	220-240V AC	Included	675 lm	416 lm	3000K	90	110°	0,70 kg
VS01WW MBK	MBK	SMD 3030 OSRAM	10W	220-240V AC	Included	675 lm	416 lm	3000K	90	110°	0,70 kg
VS01NW MWH	MWH	SMD 3030 OSRAM	10W	220-240V AC	Included	810 lm	445 lm	4000K	90	110°	0,70 kg
VS01NW MBK	MBK	SMD 3030 OSRAM	10W	220-240V AC	Included	810 lm	445 lm	4000K	90	110°	0,70 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE