

xmini LED IP44



EN
Linear light fittings for interior, equipped with SMD LEDs modules.

Housing and fixing element of aluminum profile, electrostatically painted.

End caps of die-cast aluminium, electrostatically painted. Diffuser of opal PMMA.

Constant current LED driver included.

Block of terminals 2P (10A/250V/2,5mm²).

Range of applications

Interior lighting, especially above or on the sides of the mirrors.

RO

Corpuri de iluminat liniare pentru montaj în interior, echipate cu module cu LED-uri SMD.

Corpul și elementul de fixare din profil de aluminiu, vopsite în câmp electrostatic.

Elementele de capăt de aluminiu turnat, vopsite în câmp electrostatic.

Dispersor din PMMA opal.

Alimentator LED în curent constant inclus.

Clemă de conexiuni 2P (10A/250V/2,5mm²).

Aplicații

Iluminatul de interior, în special deasupra sau în părțile laterale ale oglinzilor.

IT

Apparecchi lineari per interni, equipaggiati con moduli a LED SMD.

Corpo ed elemento di fissaggio in profilo di alluminio, verniciati a polveri.

Tappi di chiusura in pressofusione di alluminio, verniciati a polveri.

Diffusore in PMMA opale.

Alimentatore LED in corrente costante incluso.

Morsettiere 2P (10A/250V/2,5mm²).

Campi di applicazione

Illuminazione d'interni, particolarmente indicate per il montaggio lato o sopra specchi.



3 YEARS WARRANTY



MN01

FINISHING AVAILABLE

MWH



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
MN01WWP MWH	MWH	SMD 2835 SAN'AN	15W	220-240V AC	Included	1250 lm	1109 lm	3000K	80	160°	0,52 kg
MN01NWP MWH	MWH	SMD 2835 SAN'AN	15W	220-240V AC	Included	1330 lm	1177 lm	4000K	80	160°	0,52 kg

