

xring

**3 YEARS
WARRANTY**



LED



IP54



EN

Recessed decorative spots, dustproof and water-proof (IP54), equipped with COB LEDs.
Heat sink and support of die-cast aluminum, electrostatically painted.
Opal polycarbonate diffuser with two concentric circles of aluminum, electrostatically painted.
Constant current LED driver has to be ordered separately.
Range of applications
Decorative lighting in bathroom and other interior humid environments.
Exterior decorative lighting of soffits.

RO

Spoturi decorative încastrate, protejate la praf și umiditate (IP54) echipate cu LED-uri COB.
Radiator și suport din aluminiu turnat, vopsit în câmp electrostatic.
Dispersor din policarbonat opal cu două cercuri centrice din aluminiu vopsite în câmp electrostatic.
Alimentator în curent constant se comandă separat.
Aplicații
Illuminatul decorativ în băi sau alte spații cu umiditate din interior.
Illuminatul decorativ de exterior în copertine.



IT

Incassi decorativi, protetti contro polvere e umidità (IP54), equipaggiati con LED COB.
Raffreddatore e supporto in pressofusione di alluminio, verniciato a polveri.
Diffusore in policarbonato opalino con due cerchi concentrici in alluminio, verniciati a polveri.
Alimentatore a corrente costante da ordinare separatamente.
Campi di applicazione
Illuminazione decorativa per bagni e altre aree umide interne.
Illuminazione decorativa in esterni di pensiline e controsoffittature.

RG01

FINISHING AVAILABLE

MWH



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
RG01WW MWH	MWH	COB BRIDGELUX	1x10W	500 mA	Excluded	848 lm	317 lm	3000K	90	large	Ø67 mm	0.28 kg
RG01NW MWH	MWH	COB BRIDGELUX	1x10W	500 mA	Excluded	899 lm	395 lm	4000K	80	large	Ø67 mm	0.28 kg

Recommended CC Drivers



AT201 ATD500.12