

xcam

**3 YEARS
WARRANTY**



EN

Recessed light fittings, for interior, fixed or adjustable, equipped with COB LEDs.
Frame, housing, gimbal system and heat sink of die-cast aluminum.

Reflector of chromed polycarbonate and clear glass diffuser.

Constant current LED driver has to be ordered separately.

Range of applications

General or accent lighting in commercial areas, museums and other exhibition spaces, residential areas.

RO

Corpuri de iluminat pentru montaj încastrat în interior, fixe sau orientabile, echipate cu LED-uri COB.

Rama, corpul, sistemul cardanic și radiatorul din aluminiu turnat.

Reflector din policarbonat cromat, dispersor din sticlă clară.

Alimentatorul în curent constant se comandă separat.

Aplicații

Iluminatul general sau de accent în spații comerciale, muzee și alte spații de expunere, zone rezidențiale.

IT

Incassi fissi o orientabili per interni, dotati di LED COB.

Telaio, corpo, sistema cardanico e dissipatore in alluminio pressofuso.

Riflettore in policarbonato cromato, diffusore in vetro trasparente.

Alimentatore a corrente costante da ordinare separatamente.



Campi di applicazione

Illuminazione generale o d'accento in musei e altri spazi espositivi, aree residenziali.

CA01

FINISHING AVAILABLE

MWH AL-AN



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
● CAD1WW40 MWH	MWH	COB BRIDGELUX	1x7W	350 mA	Excluded	618 lm	422 lm	3000K	90	40°	Ø48 mm	0,15 kg
● CAD1NW40 MWH	MWH	COB BRIDGELUX	1x7W	350 mA	Excluded	655 lm	473 lm	4000K	80	40°	Ø48 mm	0,15 kg
● CAD1WW40 AL	AL-AN	COB BRIDGELUX	1x7W	350 mA	Excluded	618 lm	422 lm	3000K	90	40°	Ø48 mm	0,15 kg
● CAD1NW40 AL	AL-AN	COB BRIDGELUX	1x7W	350 mA	Excluded	655 lm	473 lm	4000K	80	40°	Ø48 mm	0,15 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE



Recommended CC Drivers



CA02

FINISHING AVAILABLE

MWH AL-AN



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight	
CA02WW40 MWH	MWH	COB BRIDGELUX	1x15W	700 mA	Excluded	1241 lm	968 lm	3000K	90	40°	Ø105 mm	0.71 kg
CA02NW40 MWH	MWH	COB BRIDGELUX	1x15W	700 mA	Excluded	1302 lm	1113 lm	4000K	80	40°	Ø105 mm	0.71 kg
CA02WW40 AL	AL-AN	COB BRIDGELUX	1x15W	700 mA	Excluded	1241 lm	968 lm	3000K	90	40°	Ø105 mm	0.71 kg
CA02NW40 AL	AL-AN	COB BRIDGELUX	1x15W	700 mA	Excluded	1302 lm	1113 lm	4000K	80	40°	Ø105 mm	0.71 kg

Recommended CC Drivers





AT301

ATD700.18

CA03

FINISHING AVAILABLE

MWH AL-AN



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight	
● CA03WW40 MWH	MWH	COB BRIDGELUX	1x7W	350 mA	Excluded	618 lm	514 lm	3000K	90	40°	Ø94 mm	0.29 kg
CA03NW40 MWH	MWH	COB BRIDGELUX	1x7W	350 mA	Excluded	655 lm	576 lm	4000K	80	40°	Ø94 mm	0.29 kg
CA03WW40 AL	AL-AN	COB BRIDGELUX	1x7W	350 mA	Excluded	618 lm	514 lm	3000K	90	40°	Ø94 mm	0.29 kg
CA03NW40 AL	AL-AN	COB BRIDGELUX	1x7W	350 mA	Excluded	655 lm	576 lm	4000K	80	40°	Ø94 mm	0.29 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

Recommended CC Drivers



AT102

ATD350.09