

xtwist

3 YEARS WARRANTY



EN

Recessed spot lights, for ceiling or wall mounting, for interior use, equipped with power LEDs.
Housing and frame of extruded aluminum.
Frame with brushed aluminum finishing or electrostatically painted.
FRESNEL polycarbonate lens.
Constant current LED has to be ordered separately.
Range of applications
General or accent lighting, guiding on circulation areas.

RO

Spoturi de încastrat cu montaj în tavan sau perete, pentru interior, echipate cu LED-uri de putere.
Corpul și rama din aluminiu extrudat.
Rama cu finisaj aluminiu periat sau vopsită în câmp electrostatic.
Lentilă FRESNEL din policarbonat.
Alimentatorul în curent constant se comandă separat.
Aplicații
Iluminatul general sau iluminatul de accent și marcare a căilor de circulație.


IT

Faretti ad incasso a parete o a soffitto, per interni, equipaggiati con LED di potenza.
Corpo e telaio di alluminio estruso.
Telaio con finitura alluminio spazzolato o verniciato a polveri.
Lente FRESNEL in policarbonato.
Alimentatore a corrente costante da ordinare separatamente.
Campi di applicazione
Illuminazione generale, illuminazione d'accento e segna passo in aree di transito.

TW01

FINISHING AVAILABLE

MWH BA



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
TW01WW40 MWH	MWH	POWER LED CREE	1x3W	700 mA	Excluded	165 lm	119 lm	3000K	80	40°	Ø38 mm	0,05 kg
TW01NW40 MWH	MWH	POWER LED CREE	1x3W	700 mA	Excluded	215 lm	155 lm	4000K	80	40°	Ø38 mm	0,05 kg
TW01WW40 BA	BA	POWER LED CREE	1x3W	700 mA	Excluded	165 lm	119 lm	3000K	80	40°	Ø38 mm	0,05 kg
TW01NW40 BA	BA	POWER LED CREE	1x3W	700 mA	Excluded	215 lm	155 lm	4000K	80	40°	Ø38 mm	0,05 kg


Recommended CC Drivers



TW02

FINISHING AVAILABLE

MWH BA



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
TW02WW40 MWH	MWH	POWER LED CREE	1x3W	700 mA	Excluded	165 lm	119 lm	3000K	80	40°	Ø38 mm	0,06 kg
TW02NW40 MWH	MWH	POWER LED CREE	1x3W	700 mA	Excluded	215 lm	155 lm	4000K	80	40°	Ø38 mm	0,06 kg
TW02WW40 BA	BA	POWER LED CREE	1x3W	700 mA	Excluded	165 lm	119 lm	3000K	80	40°	Ø38 mm	0,06 kg
TW02NW40 BA	BA	POWER LED CREE	1x3W	700 mA	Excluded	215 lm	155 lm	4000K	80	40°	Ø38 mm	0,06 kg

Recommended CC Drivers

