


xstone maxi





EN
Series of surface mounted light fittings, equipped with power SMD LEDs, with reduced luminance due to the positions of LEDs and the shape of the reflectors.
Gypsum or concrete structure with fixing clamp of steel board.
High-gloss faceted plastic reflector.
Diffusers of clear polycarbonate, optical system UGR<16.
Decorative rings of aluminum, electrostatically painted.
Constant current LED driver delivered with the luminaire.
Range of applications
Lighting for the small shops, hotels, museums or other exhibition areas.
General interior lighting.

RO
Serie de corpuri de iluminat cu montaj aparent, echipate cu LED-uri SMD de putere.
Corpurile de iluminat au luminanțe reduse, datorită poziției rețrate a LED-urilor și formei reflectoarelor.
Structură din gips sau ciment cu bridă de fixare din tablă de oțel.
Reflectoare din plastic oglindat și fațetat.
Dispersoare din policarbonat clar, sistem optic UGR<16.
Inele decorative din aluminiu, vopsite în câmp electrostatic.
Alimentator LED în curent constant livrat împreună cu corpul de iluminat.
Aplicații
Iluminatul spațiilor comerciale, hotelurilor, muzeelor sau al altor spații de expunere.
Iluminatul general de interior.

IT
Serie di apparecchi per montaggio a soffitto, equipaggiati da LED SMD di potenza.
Questi apparecchi hanno bassa luminanza grazie alle posizioni dei LED e alla forma dei riflettori.
Struttura in gesso o cemento con staffa di montaggio in acciaio.
Riflettori in plastica specchiata e sfaccettata.
Diffusori in policarbonato trasparente, sistema ottico UGR<16.
Anelli decorativi in alluminio, verniciati a polveri.
Alimentatore LED a corrente costante fornito con l'apparecchio.
Campi di applicazione
Illuminazione per negozi, alberghi, musei e aree espositive.
Illuminazione generale di interni.

STN04



FINISHING AVAILABLE



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
STN04WW GP/MBK	GP/MBK	SMD 5050 BRIDGELUX	4.2W	220-240V AC	Included	410 lm	257 lm	3000K	90	38°	0.78 kg
STN04WW CM/MBK	CM/MBK	SMD 5050 BRIDGELUX	4.2W	220-240V AC	Included	410 lm	257 lm	3000K	90	38°	0.86 kg

STN05

FINISHING AVAILABLE





Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
STN05WW GP/MBK	GP/MBK	SMD 5050 BRIDGELUX	11.6W	220-240V AC	Included	1230 lm	727 lm	3000K	90	38°	1.57 kg
STN05WW CM/MBK	CM/MBK	SMD 5050 BRIDGELUX	11.6W	220-240V AC	Included	1230 lm	727 lm	3000K	90	38°	1.57 kg

STN06

FINISHING AVAILABLE

- GP/MBK**
- CM/MBK**



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
STN06WW GP/MBK	GP/MBK	SMD 5050 BRIDGELUX	14.7W	220-240V AC	Included	1640 lm	896 lm	3000K	90	38°	2,46 kg
STN06WW CM/MBK	CM/MBK	SMD 5050 BRIDGELUX	14.7W	220-240V AC	Included	1640 lm	896 lm	3000K	90	38°	2,46 kg