

xshop LED

3 YEARS
WARRANTY



EN

Adjustable projectors for interior mounting, for three circuits track model, equipped with OSRAM PrevaLED COIN T11 AC modules.

Housing made of extruded aluminum, electrostatically painted.

Polycarbonate lens, with 24° and 40° dispersion angles.

Equipped with three circuit track connector, 250V, 16A or can be mounted directly to the ceiling through the basis plate TKN1016.

Range of applications

Orientability of light allows use in general or detail lighting of specialized stores, shops or art galleries.

RO

Proiectoare orientabile, de interior, pentru șină cu trei circuite echipate cu module OSRAM PrevaLED COIN T11 AC. Carcasă din aluminiu extrudat, vopsită în câmp electrostatic.

Lentilă din policarbonat, având unghiul de dispersie de 24° sau 40°.

Este prevăzut cu adaptor pentru șină cu trei circuite, 250V, 16A sau se poate monta direct pe tavan cu ajutorul plăcii de bază TKN1016.

Aplicații

Datorită libertăților de mișcare pot fi folosite pentru iluminatul general sau de detaliu al magazinelor specializate, al spațiilor comerciale sau al galeriilor de artă.

IT

Proiettori orientabili da interni, per binari a tre circuiti equipaggiati con moduli OSRAM PrevaLED COIN T11 AC. Carcasa in alluminio estruso, verniciato a polveri. Lenti in policarbonato con angoli di 24° o 40°.

Fornito con adattore per binario a tre circuiti, 250V, 16A, può essere montato a soffitto tramite accessorio TKN1016.

Campi di applicazione

Grazie alla loro capacità di orientamento sono ideali per illuminazione generale e illuminazione di spazi commerciali, showroom, gallerie d'arte.



Art. TKN1016

Ceiling adapter.

Adaptor pentru montaj pe plafon.


Adattatore montaggio a plafone.

SP02/03



FINISHING AVAILABLE

MWH BK S



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	Optics	CRI	Weight
SP02WW24 MWH	MWH	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1225 lm	1225 lm	3000K	24°	83	1.05 kg
SP02WW24 S	S	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1225 lm	1225 lm	3000K	24°	83	1.05 kg
SP02WW24 BK	BK	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1225 lm	1225 lm	3000K	24°	83	1.05 kg
SP02NW24 MWH	MWH	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1388 lm	1388 lm	4000K	24°	83	1.05 kg
SP02NW24 S	S	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1388 lm	1388 lm	4000K	24°	83	1.05 kg
SP02NW24 BK	BK	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1388 lm	1388 lm	4000K	24°	83	1.05 kg
SP02WW40 MWH	MWH	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1241 lm	1241 lm	3000K	40°	83	1.05 kg
SP02WW40 S	S	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1241 lm	1241 lm	3000K	40°	83	1.05 kg
SP02WW40 BK	BK	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1241 lm	1241 lm	3000K	40°	83	1.05 kg
SP02NW40 MWH	MWH	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1337 lm	1337 lm	4000K	40°	83	1.05 kg
SP02NW40 S	S	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1337 lm	1337 lm	4000K	40°	83	1.05 kg
SP02NW40 BK	BK	PrevaLED COIN 111 AC	1x15.5W	198-264V AC	Included	1337 lm	1337 lm	4000K	40°	83	1.05 kg
SP03WW24 MWH	MWH	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1696 lm	1696 lm	3000K	24°	83	1.05 kg
SP03WW24 S	S	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1696 lm	1696 lm	3000K	24°	83	1.05 kg
SP03WW24 BK	BK	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1696 lm	1696 lm	3000K	24°	83	1.05 kg
SP03NW24 MWH	MWH	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1918 lm	1918 lm	4000K	24°	83	1.05 kg
SP03NW24 S	S	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1918 lm	1918 lm	4000K	24°	83	1.05 kg
SP03NW24 BK	BK	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1918 lm	1918 lm	4000K	24°	83	1.05 kg
SP03WW40 MWH	MWH	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1739 lm	1739 lm	3000K	40°	83	1.05 kg
SP03WW40 S	S	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1739 lm	1739 lm	3000K	40°	83	1.05 kg
SP03WW40 BK	BK	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1739 lm	1739 lm	3000K	40°	83	1.05 kg
SP03NW40 MWH	MWH	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1892 lm	1892 lm	4000K	40°	83	1.05 kg
SP03NW40 S	S	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1892 lm	1892 lm	4000K	40°	83	1.05 kg
SP03NW40 BK	BK	PrevaLED COIN 111 AC	1x22.5W	198-264V AC	Included	1892 lm	1892 lm	4000K	40°	83	1.05 kg

