

xia

3 YEARS WARRANTY



EN

Ceiling lamps for exterior, equipped with COB LED, high luminous efficiency, housing of die-cast aluminum electrostatically painted in mat white or dark grey, diffuser of transparent tempered glass.

Range of applications

General lighting in bathrooms and other interior wet environments. Exterior general lighting in soffits of buildings.

RO

Plafoniere pentru exterior echipate cu LED COB, cu eficiență luminoasă mare, structură din aluminiu turnat sub presiune, vopsit în câmp electrostatic alb mat sau gri închis, dispersor din sticlă temperată transparentă.

Aplicații

Iluminatul general în băi sau alte spații umede din interior. Iluminatul general de exterior în copertinele clădirilor.

IT

Plafoniere per esterni equipaggiate con LED COB ad alta efficienza luminosa, corpo in pressofusione di alluminio verniciato a polveri bianco opaco o grigio scuro, diffusore in vetro temperato trasparente.


Campi di applicazione

Illuminazione generale, bagni e altre aree umide in interni. Illuminazione esterna di persilne e controsoffittature di edifici.

XIA ROUND

FINISHING AVAILABLE

MWH DG




Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
9580	MWH	COB LED LUMENS	1x20W	220-240V AC	Included	2390 lm	1616 lm	3000K	80	34°	0.68 kg
9581	DG	COB LED LUMENS	1x20W	220-240V AC	Included	2390 lm	1616 lm	3000K	80	34°	0.68 kg
90029	MWH	COB LED LUMENS	1x20W	220-240V AC	Included	2600 lm	1778 lm	4000K	80	34°	0.68 kg
90030	DG	COB LED LUMENS	1x20W	220-240V AC	Included	2600 lm	1778 lm	4000K	80	34°	0.68 kg

XIA SQUARE

FINISHING AVAILABLE

MWH DG



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
9582	MWH	COB LED LUMENS	1x20W	220-240V AC	Included	2390 lm	1616 lm	3000K	80	34°	0.76 kg
9583	DG	COB LED LUMENS	1x20W	220-240V AC	Included	2390 lm	1616 lm	3000K	80	34°	0.76 kg
90031	MWH	COB LED LUMENS	1x20W	220-240V AC	Included	2600 lm	1778 lm	4000K	80	34°	0.76 kg
90032	DG	COB LED LUMENS	1x20W	220-240V AC	Included	2600 lm	1778 lm	4000K	80	34°	0.76 kg