

xkrio

3 YEARS WARRANTY



EN

Series of ground recessed light spots for pedestrian areas, equipped with power LEDs.

Delivered sealed, with silicone gaskets and equipped with recessed boxes of thermoplastic material with high mechanical and thermal resistance.

Body of extruded anodised aluminum, frame of AISI 316 stainless steel.

Diffuser of frosted glass.

Constant current LED driver (has to be ordered separately) must be installed into a minimum IP67 case.

Range of applications

Exterior decorative lighting, building facades, parks, public or private gardens.

Marking of the pedestrian or auto circulation areas.

RO

Serie de spoturi încastrate în pardoseală, pietonale, echipate cu LED-uri de putere.

Livrate capsulate, cu garnituri de etanșare din silicon și echipate cu doze de încastare din material plastic rezistent termic.

Corp din aluminiu extrudat și anodizat, rama din inox AISI 316.

Dispensur din sticlă satinată.

Alimentator în curent constant care se comandă separat și trebuie instalat într-o doză având gradul minim de protecție IP67.

Aplicații

Iluminatul decorativ de exterior, parcuri, grădini publice și private.

Marcarea zonelor de circulație pietonală.

IT

Serie di faretti da incasso a filo terreno, per aree pedonali, equipaggiati con LED di potenza.

Consegnati sigillati, con guarnizioni in gomma silconica, completi di controcasse in plastica ad alta resistenza meccanica e termica.

Corpo in alluminio estruso e anodizzato, telaio in acciaio inossidabile AISI 316.

Diffusore in vetro satinato.

Alimentatore in corrente costante, da ordinare separatamente, deve essere montato in una scatola con grado minimo di protezione IP67.

Campi di applicazione

Illuminazione decorativa esterna, parchi, giardini pubblici e privati.

Marcatura aree a traffico pedonale.

KR01

FINISHING AVAILABLE




KR02

FINISHING AVAILABLE



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
KR01WW120	SS	POWER LED CREE	1x1W	350 mA	Excluded	140 lm	34 lm	3000K	80	120°	Ø20 mm	0,04 kg
KR01CW120	SS	POWER LED CREE	1x1W	350 mA	Excluded	155 lm	38 lm	6000K	80	120°	Ø20 mm	0,04 kg
KR02WW120	SS	POWER LED CREE	1x1W	350 mA	Excluded	140 lm	34 lm	3000K	80	120°	Ø20 mm	0,04 kg
KR02CW120	SS	POWER LED CREE	1x1W	350 mA	Excluded	155 lm	38 lm	6000K	80	120°	Ø20 mm	0,04 kg



Recommended CC Drivers



AT350.10IP65