

# xarea

**5 YEARS WARRANTY**



## EN

Series of recessed light fittings, for indoor or outdoor mounting, dustproof and waterproof (IP65), equipped with power LEDs. Frame of die-cast aluminum, electrostatically painted.

Heat sink of die-cast aluminum.

Recessed box of steel sheet, electrostatically painted, for installation in concrete ceiling.

Decorative cover of polycarbonate, painted in mat black color. PMMA lenses.

Clear glass diffuser.

Constant current LED driver has to be ordered separately.

### Range of applications

General lighting in bathroom and other interior humid environments.

Exterior general lighting in soffits of buildings.

## RO

Serie de corpuri de iluminat cu montaj încastrat, pentru interior sau exterior, protejate la praf și umiditate (IP65), echipate cu LED-uri de putere.

Rama din aluminiu turnat, vopsită în câmp electrostatic.

Radiatorul din aluminiu turnat.

Doză de încastrare din tablă de oțel, vopsită în câmp electrostatic, pentru montajul în tavan de beton.

Masă decorativă din policarbonat vopsită în negru mat.

Lentile din PMMA.

Dispersor din sticlă clară.

Alimentatorul în curent constant se comandă separat.

### Aplicații

Iluminatul general în băi sau alte spații umede din interior.

Iluminatul general de exterior în copertinele clădirilor.

## IT

Serie di apparecchi ad incasso per interni o esterni protetti da polvere e umidità (IP65), equipaggiati con LED di potenza. Telaio in alluminio pressofuso, verniciato a polveri.

Dissipatore in alluminio pressofuso.

Scatola da incasso in lamiera d'acciaio, verniciata a polveri, per montaggio a soffitto in calcestruzzo.

Maschera decorativa porta lenti in policarbonato, verniciata in colore nero opaco.

Lenti in PMMA.

Diffusore in vetro trasparente.

Alimentatore a corrente costante da ordinare separatamente.

### Campi di applicazione

Illuminazione generale, bagni e altre aree umide in interni.

Illuminazione esterna di pensiline e controsoffittature di edifici.



## AE01

FINISHING AVAILABLE

MWH MBK



### Recommended CC Drivers





Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
AE01WW30 MWH/BK	MWH/BK	POWER LED OSRAM	3x3W	700 mA	Excluded	660 lm	417 lm	3000K	80	30°	Ø85 mm	0.50 kg
AE01NW30 MWH/BK	MWH/BK	POWER LED OSRAM	3x3W	700 mA	Excluded	705 lm	469 lm	4000K	80	30°	Ø85 mm	0.50 kg
AE01WW30 MBK/BK	MBK/BK	POWER LED OSRAM	3x3W	700 mA	Excluded	660 lm	417 lm	3000K	80	30°	Ø85 mm	0.50 kg
AE01NW30 MBK/BK	MBK/BK	POWER LED OSRAM	3x3W	700 mA	Excluded	705 lm	469 lm	4000K	80	30°	Ø85 mm	0.50 kg

## AE02

FINISHING AVAILABLE

MWH MBK





Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
AE02WW30 MWH/BK	MWH/BK	POWER LED OSRAM	6x3W	700 mA	Excluded	1320 lm	863 lm	3000K	80	30°	Ø108 mm	0.92 kg
AE02NW30 MWH/BK	MWH/BK	POWER LED OSRAM	6x3W	700 mA	Excluded	1410 lm	932 lm	4000K	80	30°	Ø108 mm	0.92 kg

## AE03

FINISHING AVAILABLE

MWH MBK



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
AE03WW30 MWH/BK	MWH/BK	POWER LED OSRAM	12x1W	350 mA	Excluded	1460 lm	973 lm	3000K	80	30°	Ø150 mm	0.94 kg
AE03NW30 MWH/BK	MWH/BK	POWER LED OSRAM	12x1W	350 mA	Excluded	1570 lm	1107 lm	4000K	80	30°	Ø150 mm	0.94 kg