

xfollow

3 YEARS WARRANTY



EN
Waterproof wall recessed light fittings (IP65), equipped with power LEDs.
Frame of die-cast aluminum, electrostatically painted.
Heat sink of die-cast aluminum.
Transparent glass diffuser.
Constant current LED driver has to be ordered separately.
Range of applications
Indoor and outdoor decorative lighting.


RO
Corpuri de iluminat etanșe (IP65), încastrate în perete, echipate cu LED-uri de putere.
Ramă din aluminiu turnat, vopsită în câmp electrostatic.
Radiatorul din aluminiu turnat.
Dispersor din sticlă transparentă.
Alimentator la curent constant se comandă separat.
Aplicații
Iluminatul decorativ în interior sau exterior.

IT
Apparecchi da incasso a parete, protetti da polvere e umidità (IP65), equipaggiati con LED di potenza.
Telaio in alluminio pressofuso, verniciato a polveri.
Dissipatore in alluminio pressofuso.
Diffusore in vetro trasparente.
Alimentatore a corrente costante da ordinare separatamente.
Campi di applicazione
Illuminazione decorativa per interni ed esterni.

FW01

FINISHING AVAILABLE


MWH S



FW02

FINISHING AVAILABLE

MWH S



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Ø	Weight
FW01NW MWH	MWH	POWER LED CREE	1x3W	700 mA	Excluded	240 lm	87 lm	4000K	80	Asymmetrical	Ø45 mm	0.13 kg
FW01NW S	S	POWER LED CREE	1x3W	700 mA	Excluded	240 lm	87 lm	4000K	80	Asymmetrical	Ø45 mm	0.13 kg
FW02NW MWH	MWH	POWER LED CREE	1x3W	700 mA	Excluded	240 lm	131 lm	4000K	80	Asymmetrical	Ø45 mm	0.14 kg
FW02NW S	S	POWER LED CREE	1x3W	700 mA	Excluded	240 lm	131 lm	4000K	80	Asymmetrical	Ø45 mm	0.14 kg

Recommended CC Drivers

