

xkey

3 YEARS WARRANTY



EN

Waterproof wall recessed light fittings (IP65), equipped with power LEDs.
Body of die-cast anodized aluminum.
Silicone gaskets.
Recessed box of plastic with high mechanical and thermal resistance.
Satin glass diffuser.
Constant current LED driver has to be ordered separately.

Range of applications

Indoor and outdoor decorative lighting.

RO

Corpuri de iluminat etanșe (IP65), încastrate în perețe, echipate cu LED-uri de putere.
Corp din aluminiu turnat finisaj aluminiu anodizat.
Garnituri de etanșare din silicon.
Doză din material plastic cu înaltă rezistență termică și mecanică.
Dispersor din sticlă satinată.
Alimentatorul în curent constant se comandă separat.

Aplicații

Iluminatul decorativ în interior sau exterior.

IT

Apparecchi da incasso a parete, protetti da polvere e umidità (IP65), equipaggiati con LED di potenza.
Corpo in alluminio pressofuso e anodizzato.
Guarnizioni in gomma siliconica.
Controcassa in termoplastica ad alta resistenza meccanica e termica.
Diffusore in vetro satinato.
Alimentatore a corrente costante da ordinare separatamente.



Campi di applicazione

Illuminazione decorativa per interni ed esterni.

KY01

FINISHING AVAILABLE

MWH AL-AN



Code	Finishing	LED type	Power	Input current	Driver	LED Flux	System Flux	CCT	CRI	Optics	Weight
KY01W MWH	MWH	POWER LED CREE	1x1W	350 mA	Excluded	140 lm	20 lm	3000K	80	Circular slot of light	Ø45 mm 0,28 kg
● KY01W AL	AL-AN	POWER LED CREE	1x1W	350 mA	Excluded	140 lm	20 lm	3000K	80	Circular slot of light	Ø45 mm 0,28 kg
● KY01W MWH	MWH	POWER LED CREE	1x1W	350 mA	Excluded	155 lm	27 lm	4000K	80	Circular slot of light	Ø45 mm 0,28 kg
● KY01W AL	AL-AN	POWER LED CREE	1x1W	350 mA	Excluded	155 lm	27 lm	4000K	80	Circular slot of light	Ø45 mm 0,28 kg

● ORDERED UPON REQUEST / DISPONIBIL DOAR LA COMANDĂ / DISPONIBILE SOLO SU ORDINAZIONE

Recommended CC Drivers



AT350.10IP65