

xghost IP65

**3 YEARS
WARRANTY**



EN
Waterproof wall recessed light fittings (IP65), equipped with SMD LEDs.
Housing of die-cast aluminum, electrostatically painted.
Recessed box in polycarbonate.
Transparent polycarbonate diffuser.
LED driver included.
Rubber seal at cable crossing.
Cable length 10cm, 3x0.75 mm².
Range of applications
Indoor and outdoor decorative lighting.



RO
Corpuri de iluminat etanșe (IP65), încastrate în perete, echipate cu un LED-uri SMD.
Carcasă din aluminiu turnat, vopsită în câmp electrostatic.
Doză de încastrare din polycarbonat.
Dispersor din polycarbonat transparent.
Alimentator pentru LED-uri inclus.
Garnitură din cauciuc la trecerea cablului de alimentare.
Lungime cablu 10cm, 3x0,75 mm².
Aplicații
Iluminatul decorativ in interior sau exterior.

IT
Apparecchi da incasso a parete, protetti da polvere e umidità (IP65), equipaggiati con LED SMD.
Corpo in alluminio pressofuso, verniciato a polveri.
Scatola da incasso in polycarbonato.
Diffusore in polycarbonato trasparente.
Alimentatore LED incluso.
Guarnizione in gomma per passaggio cavo di alimentazione.
Lunghezza cavo 10cm, 3x0.75 mm².
Campi di applicazione
Illuminazione decorativa per interni ed esterni.

GS02

FINISHING AVAILABLE

MWH MBK



Code	Finishing	LED type	Power	Input voltage	Driver	LED Flux	System Flux	CCT	CRI	Optics	⌀	Weight
GS02WWIP65 MWH	MWH	SMD 5730 EPISTAR	2W	100-240V AC	Included	180 lm	89 lm	3000K	80	Asymmetrical	74x74 mm	0.20 kg
GS02NWIP65 MWH	MWH	SMD 5730 EPISTAR	2W	100-240V AC	Included	192 lm	98 lm	4000K	80	Asymmetrical	74x74 mm	0.20 kg
GS02WWIP65 BK	MBK	SMD 5730 EPISTAR	2W	100-240V AC	Included	180 lm	89 lm	3000K	80	Asymmetrical	74x74 mm	0.20 kg
GS02NWIP65 BK	MBK	SMD 5730 EPISTAR	2W	100-240V AC	Included	192 lm	98 lm	4000K	80	Asymmetrical	74x74 mm	0.20 kg