



Illuminated pushbutton actuator, green, maintained, +filament lamp 24V

Part no. Q18LTR-GN/WB
086413

General specifications		
Product name		Eaton Moeller® series RMQ16 Illuminated pushbutton actuator
Part no.		Q18LTR-GN/WB
EAN		4015080864134
Product Length/Depth		59 millimetre
Product height		18 millimetre
Product width		18 millimetre
Product weight		0.009 kilogram
Certifications		IEC/EN 60947 UL CSA UL 508 CSA-C22.2 No. 14-05 IEC/EN 60947-5 CSA Class No.: 3211-03 UL File No.: E29184 CSA File No.: 46552 UL Category Control No.: NKCR CE
Product Tradename		RMQ16
Product Type		Illuminated pushbutton actuator
Product Sub Type		None
Features & Functions		
Bezel color		Black
Bezel material		Plastic
Design		Flat
Fitted with:		Filament bulb (24 V)
Inscription		Blank
General information		
Degree of protection		NEMA 1 IP65
Degree of protection (front side)		IP65 NEMA 1
Lifespan, mechanical		30,000,000 Operations
Opening diameter		16 mm
Operating frequency		1800 Operations/h
Overvoltage category		III
Pollution degree		3
Product category		RMQ16
Size		Front dimensions: 18 x 18 mm
Rated impulse withstand voltage (Uimp)		800 V AC
Suitable for		Illumination
Terminal capacity		0.5 - 1.0 mm²
Terminal size		2.8 x 0.8 mm to DIN 46244, Blade terminal 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors
Type		Illuminated pushbutton actuator
Ambient conditions, mechanical		
Mounting position		As required
Shock resistance		40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Climatic environmental conditions		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C

Ambient operating temperature (enclosed) - max			40 °C
Climatic proofing			Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
Electrical rating			
Rated insulation voltage (Ui)			250 V
Rated operational voltage (Ue) at AC - max			24 V
Actuator			
Actuating force			4 N
Actuator color			Green
Actuator function			Maintained Switching function latching
Contacts			
Control circuit reliability			1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA) 1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)
Communication			
Connection to SmartWire-DT			No
Design verification			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdis			0 W
Heat dissipation per pole, current-dependent Pvid			0 W
Rated operational current for specified heat dissipation (In)			0 A
Static heat dissipation, non-current-dependent Pvs			1 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecl@ss13-27-37-12-10 [AKF028019])			
Colour button			Green
Number of command positions			1
Construction type lens			Square
Hole diameter		mm	16

Width opening		mm	0
Height opening		mm	0
Type of button			Flat
Suitable for illumination			Yes
With protective cover			No
Labelled			No
Switching function latching			Yes
Spring-return			No
With front ring			No
Material front ring			Plastic
Colour front ring			Black
Degree of protection (IP), front side			IP65
Degree of protection (NEMA), front side			1