



Barrier Strip

RW 85 F

EAN Code: 4013339237708
Smallest packaging unit: 10 x 3 m
quantity unit: m M

the photorealistic images are to be considered as reference images



Article Description

Barrier strip, 80x3000 mm, t=0,9 mm, steel, hot dip galvanised DIN EN ISO 1461, incl. accessories

Incl. accessories

3 meter = 1 piece		- lowest delivery unit	- preferred delivery unit
Model No.	Description	quantity	
1-FLM 6X12 F	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, hot dip galvanised DIN EN ISO 1461	4 pcs.	
30 meter = 1 bundle		✓ lowest delivery unit	✓ preferred delivery unit
Model No.	Description	quantity	
FLM 6X12 F	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, hot dip galvanised DIN EN ISO 1461	40 pcs.	
2100 meter = 1 rack		- lowest delivery unit	- preferred delivery unit
Model No.	Description	quantity	
FLM 6X12 F	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, hot dip galvanised DIN EN ISO 1461	2.800 pcs.	

Technical Datasheet

Cable Tray System

RW 85 F

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	854 g / m
Weight in kg per 100	85 kg / 100m

Physical Article Dimensions

Height	80.00 mm
Width	24.00 mm
Depth/length	3000 mm

Packing Dimension

30 meters = 1 bundle		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	3000 mm	Width	240 mm	Height	80.00 mm
Gross weight	26 kg	Volume	0,058 m³		
Min. quantity	30.00 m	Max. Quantity	30.00 m		

2100 meters = 1 rack					
Lenght	3000 mm	Width	850 mm	Height	770 mm
Gross weight	1850 kg	Volume	1,964 m³		
Min. Quantity	2.100.00 m	Max. Quantity	2.100.00 m		

Tender Text

Barrier strip, with edge protection, bottom edging perforated for screw fastening and continuously profiled for mounting in bottom or retaining lugs, for separating cables and lines with different voltages and functions, equipotential bonding takes place automatically when clipped or screwed in, including proportional fastening accessories in hot-dip galvanised.

VDE certified! Use for : wire mesh trays cable trays/ladders wide span trays/ladders barrier profile holder dimensions (approx. dimensions) H x outer packaging : 80 x 24 mm

Material thickness t : 0.9 mm

Delivery length L : 3000 mm

Material : steel, hot-dip galvanised acc. to DIN EN ISO 1461

NIEDAX Model No. : RW 85 F

EP material_____ EP wage_____

Unit price/meter

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Technical Datasheet

Cable Tray System

RW 85 F

the photorealistic images are to be considered as reference images

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Connector

Model No.	Description
RTV 85 E2	Splice plate for barrier strip, 79,5x80 mm, stainless steel, material code: 1.4310