

Barrier Strip, heavy


with system perforation

RW 100-1.5 S



EAN Code: 4013339180219

Smallest packaging unit:3 m

quantity unit:m M



the photorealistic images are to be considered as reference images



Article Description

Barrier strip, 98x2998 mm, t=1,5 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Incl. accessories

3 meter = 1 piece		✓ lowest delivery unit	✓ preferred delivery unit
Model No.	Description	quantity	
FLM 6X12	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, electro galvanised according to DIN EN ISO 2081/4042, blue pass	4 pcs.	
600 meter = 1 rack		- lowest delivery unit	- preferred delivery unit
Model No.	Description	quantity	
FLM 6X12	Mushroom-head bolt M6, similar DIN 603, length 12 mm, steel, electro galvanised according to DIN EN ISO 2081/4042, blue pass	800 pcs.	

Technical Datasheet

Cable Tray System

RW 100-1.5 S

the photorealistic images are to be considered as reference images

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	1,596 kg/ m
Weight in kg per 100	160 kg/ 100m

Physical Article Dimensions

Height	98.00 mm
Width	1.50 mm
Depth/length	2950 mm

Packing Dimension

3 meters = 1 piece		✔ VP1-smallest packaging unit (PU) ✔ VP1-preferred PU			
Lenght	2950 mm	Width	2.00 mm	Height	98.00 mm
Gross weight	4,79 kg	Volume	0,000 m³		
Min. quantity	3.00 m	Max. Quantity	3.00 m		
600 meters = 1 rack					
Lenght	2950 mm	Width	850 mm	Height	670 mm
Gross weight	1045 kg	Volume	1,680 m³		
Min. Quantity	600.00 m	Max. Quantity	600.00 m		

Tender Text

Barrier strip, profiled, with system perforation in the base flange and additional Elbow to protect cables during cable pulling, for walkable cable trays, for stepless division of the tray width and for separating cables and lines with different voltages and functions, including proportionate fixing accessories. Minimum number of barrier strips to support the walkable cover: Cover width 100 mm = 0 pieces Cover width 200 mm = 0 pieces Cover width 300 mm = 1 piece for a max. compartment size of 200 mm Cover width 400 mm = 1 piece for a max. compartment size of 200 mm Cover width 500 mm = 2 pieces for a max. compartment size of 200 mm Cover width 600 mm = 2 pieces for a max. compartment size of 200 mm Equipotential bonding is achieved by screwing to the cable tray. Suitable for : walkable cable trays Dimensions (approx. dimensions) H : 98 mm Material thickness t : 1.5 mm Delivery length L : 3000 mm Material : Steel, pre-galvanised according to DIN EN 10346 NIEDAX Model no. : RW 100-1.5 S EP Material _____ EP Wage _____ Unit price/metre

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Technical Datasheet

Cable Tray System

RW 100-1.5 S

the photorealistic images are to be considered as reference images

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059