


Cable Trunking

with perforated bottom, incl. cover

LLK 60.060

EAN Code: 4013339509102
Smallest packaging unit: 6 x 2 m
quantity unit: m M

the photorealistic images are to be considered as reference images



Article Description

Cable protection duct with cover, 60x60x2000 mm, steel, pre-galvanised according to DIN EN 10346

Additional Price Information

Article group	N16
quantity unit	m

Weight

Weight per quantity unit	1,748 kg / m
Weight in kg per 100	175 kg / 100m

Physical Article Dimensions

Height	60.00 mm
Width	60.60 mm
Depth/length	2000 mm

Technical Datasheet

Cable protection duct

LLK 60.060

the photorealistic images are to be considered as reference images

Packing Dimension

12 meters = 1		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	2020 mm	Width	150.00 mm	Height	125.00 mm
Gross weight	22 kg	Volume	0,038 m³		
Min. quantity	12.00 m	Max. Quantity	12.00 m		

432 meters = 1 rack					
Lenght	2000 mm	Width	1162 mm	Height	1120 mm
Gross weight	877 kg	Volume	2,603 m³		
Min. Quantity	432.00 m	Max. Quantity	432.00 m		

Tender Text

Cable protection duct, with snap-on cover and single-row fastening holes in the duct bottom, the equipotential bonding of the covers is carried out automatically when the covers are snapped on, accessories for equipotential bonding, two splice plates LST... per joint, must be ordered separately.

VDE certified!

Dimensions (approx. dimensions)

Height H x width W : 60 x 60 mm

single row bottom perforation : 4.2 x 12 and
7 x 15 mm

Bottom hole distance grid dimension : 250 mm

Delivery length L : 2000 mm

Usable cross-section : 3182 mm²

Material : steel, pre-galvanised acc. to DIN EN 10346

NIEDAX model no. : LLK 60.060

EP material _____ EP wage _____

Unit price/meter

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Related items

Barrier strip

Model No.	Description
TPH 60	Barrier profile holder, channel depth 59 mm, steel, pre-galvanised according to DIN EN 10346
TPS 50	Barrier strip, height 11 mm, depth 50 mm, length 1996 mm, steel, pre-galvanised according to DIN EN 10346

Technical Datasheet

Cable protection duct

LLK 60.060

the photorealistic images are to be considered as reference images

Related items

Connector

Model No.	Description
LST 60	Splice plate with flat plug, for height 60 mm, steel, pre-galvanised according to DIN EN 10346