

Set-Threaded End M8

with rope diameter 3 mm, including drop-in anchor

GAG8-3/10

EAN Code: 4013339933501
 Smallest packaging unit:10 pcs.

the photorealistic images are to be considered as reference images



Article Description

GRIPPLE, set-threaded end M8, rope-Ø 3 mm, rope length 10 m, steel, zinc coating and chromate

Additional Price Information

Article group	N12
quantity unit	pcs.

Weight

Weight per quantity unit	405 g / pcs.
Weight in kg per 100	40 kg / 100pcs.

Packing Dimension

10 pieces = 1 bag		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	330 mm	Width	100.00 mm	Height	460 mm
Gross weight	4,05 kg	Volume	0,015 m³		
Min. quantity	10.00 pcs.	Max. Quantity	10.00 pcs.		

Tender Text

Technical Datasheet

Gripple set

GAG8-3/10

the photorealistic images are to be considered as reference images

Tender Text

GRIPPLE Set threaded end M 8, including drive-in anchor, quick suspension system, versatile and ready to use, for fastening to concrete ceilings. The drop-in anchor is anchored using the GASWZ setting tool. The load-bearing capacity specifications F are only valid with sufficient anchoring to the load-bearing substrate and installation in accordance with the regulations.

Set consists of:

1 cut-to-length wire rope with threaded end

1 drop-in anchor

1 self-locking GRIPPLE for quick fastening

1 GRIPPLE adjustment/unlocking pin (1x per smallest VPE enclosed)

Dimensions (approx. dimensions)

Rope-Ø : 3 mm

Rope length L : 10 m

Threaded end/insertion anchor : M 8

Load capacity perm. F : 0.9 kN (5-fold safety against breakage)

Material Wire rope : Steel, galvanised

NIEDAX Model-No. : GAG8-3/10

EP Material_____ EP Wage_____

Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	
Customs tariff number	73121041