


U-Clamp

with pressure trough

BF 100

EAN Code: 4013339062201
Smallest packaging unit: 25 pcs.

the photorealistic images are to be considered as reference images



Article Description

U-clamp, for flat bars 4-12 mm, for 1 cable, Ø 90-100 mm, steel, hot dip galvanised DIN EN ISO 1461, with steel pressure trough

Additional Price Information

Article group	N08
quantity unit	pcs.

Weight

Weight per quantity unit	237 g / pcs.
Weight in kg per 100	24 kg / 100pcs.

Technical Datasheet

U-clamps

BF 100

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	105.00 mm
Width	171.00 mm
Depth/length	40.00 mm

Packing Dimension

25 pieces = 1 carton		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	420 mm	Width	250 mm	Height	120.00 mm
Volume	0,013 m³	Gross weight	6,47 kg		
Min. quantity	25.00 pcs.	Max. Quantity	25.00 pcs.		

1225 pieces = 1 pallet					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	332 kg	Volume	0,960 m³		
Min. Quantity	1.225.00 pcs.	Max. Quantity	1.225.00 pcs.		

Tender Text

U-clamp, with toothed clamp foot, with pressure trough and M 8 pivot bolt with multiple drive, can be used on existing steel structures.
Counter tray GWU ... please order separately.
Used for: flat steel with a thickness of 4 - 12 mm
Dimensions (approx.)
Assignment : 1 cable
for cable Ø : 90 - 100 mm
Material bracket : steel, hot-dip galvanised in accordance with DIN EN ISO 1461
Material pressure trough : steel, pre-galvanised according to DIN EN 10346
NIEDAX model no. : BF 100
EP Material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098