


U-Clamp

with pressure trough

BF 18

EAN Code: 4013339060603  
Smallest packaging unit: 100 pcs.

the photorealistic images are to be considered as reference images



Article Description

U-clamp, for flat bars 4-12 mm, for 1 cable, Ø 14-18 mm, steel, hot dip galvanised DIN EN ISO 1461, with steel pressure trough

Additional Price Information

|               |      |
|---------------|------|
| Article group | N08  |
| quantity unit | pcs. |

Weight

|                          |                   |
|--------------------------|-------------------|
| Weight per quantity unit | 37 g / pcs.       |
| Weight in kg per 100     | 3,67 kg / 100pcs. |

# Technical Datasheet

## U-clamps

BF 18

the photorealistic images are to be considered as reference images

### Physical Article Dimensions

|              |          |
|--------------|----------|
| Height       | 22.00 mm |
| Width        | 69.00 mm |
| Depth/length | 29.00 mm |

### Packing Dimension

|                              |             |                                     |             |                    |           |
|------------------------------|-------------|-------------------------------------|-------------|--------------------|-----------|
| <b>100 pieces = 1 carton</b> |             | ✓ VP1-smallest packaging unit ( PU) |             | ✓ VP1-preferred PU |           |
| Lenght                       | 250 mm      | Width                               | 250 mm      | Height             | 100.00 mm |
| Volume                       | 0,006 m³    | Gross weight                        | 4,04 kg     |                    |           |
| Min. quantity                | 100.00 pcs. | Max. Quantity                       | 100.00 pcs. |                    |           |

|                               |               |               |               |        |         |
|-------------------------------|---------------|---------------|---------------|--------|---------|
| <b>8400 pieces = 1 pallet</b> |               |               |               |        |         |
| Lenght                        | 1200 mm       | Width         | 800 mm        | Height | 1000 mm |
| Gross weight                  | 355 kg        | Volume        | 0,960 m³      |        |         |
| Min. Quantity                 | 8.400.00 pcs. | Max. Quantity | 8.400.00 pcs. |        |         |

### Tender Text

U-clamp, with toothed clamp foot, with pressure trough and M 6 pivot bolt with multiple drive, can be used on existing steel structures.  
Counter tray GWU ... /GWS ...please order separately.  
Used for: flat steel with a thickness of 4 - 12 mm  
Dimensions (approx.)  
Assignment : 1 cable  
for cable Ø : 14 - 18 mm  
Material bracket : steel, hot-dip galvanised in accordance with DIN EN ISO 1461  
Material pressure trough : steel, pre-galvanised according to DIN EN 10346  
NIEDAX model no. : BF 18  
EP Material\_\_\_\_\_ EP Wage\_\_\_\_\_  
Unit price/piece

### Safety & Environment

|            |             |
|------------|-------------|
| REACH Date | 25.06.2025  |
| REACH Info | Conformable |
| RoHS Info  | Conformable |

### Origin & International Trade

|                       |          |
|-----------------------|----------|
| Country of origin     | DE       |
| Customs tariff number | 73269098 |