


Cable U-clamp

with pressure trough

BA 14 AL

EAN Code: 4013339071401
Smallest packaging unit: 100 pcs.

the photorealistic images are to be considered as reference images



Article Description

Cable U-clamp, for 1 cable, Ø 10-14 mm, slot width 11-12 mm, aluminium, with aluminium pressure trough

Additional Price Information

Article group	N08
quantity unit	pcs.

Weight

Weight per quantity unit	11 g / pcs.
Weight in kg per 100	1,01 kg / 100pcs.

Technical Datasheet

U-clamps

BA 14 AL

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	19.00 mm
Width	54.00 mm
Depth/length	29.00 mm

Packing Dimension

100 pieces = 1 carton		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	250 mm	Width	250 mm	Height	70.00 mm
Volume	0,004 m³	Gross weight	1,22 kg		
Min. quantity	100.00 pcs.	Max. Quantity	100.00 pcs.		

14400 pieces = 1 pallet					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	191 kg	Volume	0,960 m³		
Min. Quantity	14.400.00 pcs.	Max. Quantity	14.400.00 pcs.		

Tender Text

Hammerfoot clamp, with pressure trough and M 6 to DIN EN ISO 1207 pivot bolt with multiple drive.
The clamp can only be inserted into the C-profile rail 2910... can only be inserted from the end of the profile.
Counter tray GWA ... please order separately.
Used for: C-profile rails with 11 - 12 mm slot width
Dimensions (approx.)
Assignment : 1 cable
for cable Ø : 10 - 14 mm
Material hammerfoot stirrup : aluminium
Material tray insert : aluminium
NIEDAX model no. : BA 14 AL
EP Material_____ EP Wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	76169990