


Universal-U-Clamp

with plastic pressure trough

BUK 100

EAN Code: 4013339097708
 Smallest packaging unit:25 pcs.

the photorealistic images are to be considered as reference images



Article Description

Universal-U-clamp, for 1 cable, Ø90-100 mm, slot width 18-22 mm, steel, hot dip galvanised DIN EN ISO 1461, w. plastics pressure trough

Additional Price Information

Article group	N08
quantity unit	pcs.

Weight

Weight per quantity unit	208 g / pcs.
Weight in kg per 100	21 kg / 100pcs.

Technical Datasheet

U-clamps

BUK 100

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	105.00 mm
Width	183.00 mm
Depth/length	40.00 mm

Packing Dimension

25 pieces = 1 carton		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	480 mm	Width	280 mm	Height	140.00 mm
Volume	0,019 m³	Gross weight	6,08 kg		
Min. quantity	25.00 pcs.	Max. Quantity	25.00 pcs.		

900 pieces = 1 pallet					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	234 kg	Volume	0,960 m³		
Min. Quantity	900.00 pcs.	Max. Quantity	900.00 pcs.		

Tender Text

Universal U-clamp, including plastic pressure trough with UV protection and M 8 pivot bolt with multiple drive.
Counter tray GWU ... please order separately.
Used for: C-profile rails with 18 - 22 mm slot width
Dimensions (approx. dimensions)
Assignment : 1 cable
for cable-Ø : 90 - 100 mm
Material bracket : steel, hot-dip galvanised in accordance with DIN EN ISO 1461
Material pressure tray : Polypropylene (PP), halogen-free, with UV protection, colour black
NIEDAX Model-No. : BUK 100
EP material_____ EP wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098