





Universal-U-Clamp

with plastic pressure trough

BUK 34

EAN Code: 4013339096503
Smallest packaging unit: 100 pcs.

the photorealistic images are to be considered as reference images



Article Description

Universal-U-clamp, for 1 cable, Ø 28-34 mm, slot width 18-22 mm, steel, hot dip galvanised DIN EN ISO 1461, w. plastics pressure trough

Additional Price Information

Article group	N08
quantity unit	pcs.

Weight

Weight per quantity unit	52 g / pcs.
Weight in kg per 100	5,17 kg / 100pcs.

Technical Datasheet

U-clamps

BUK 34

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	38.00 mm
Width	94.00 mm
Depth/length	24.00 mm

Packing Dimension

100 pieces = 1 carton		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	420 mm	Width	250 mm	Height	120.00 mm
Volume	0,013 m³	Gross weight	5,71 kg		
Min. quantity	100.00 pcs.	Max. Quantity	100.00 pcs.		

4900 pieces = 1 pallet					
Lenght	1200 mm	Width	800 mm	Height	1000 mm
Gross weight	268 kg	Volume	0,960 m³		
Min. Quantity	4.900.00 pcs.	Max. Quantity	4.900.00 pcs.		

Tender Text

Universal U-clamp, including plastic pressure trough with UV protection and M 6 pivot bolt with multiple drive.
Counter tray GWU ... / GWS ... please order separately.
Used for: C-profile rails with 18 - 22 mm slot width
Dimensions (approx. dimensions)
Assignment : 1 cable
for cable-Ø : 28 - 34 mm
Material bracket: steel, hot-dip galvanised in accordance with DIN EN ISO 1461
Material pressure tray : Polypropylene (PP), halogen-free, with UV protection, colour black
Material tray insert : steel, pre-galvanised according to DIN EN 10346
NIEDAX Model-No. : BUK 34
EP material_____ EP wage_____
Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73269098