

Industrial Duct

perforated, cover not included

LI 60.060






EAN Code: 4013339531905

Smallest packaging unit: 2 m

quantity unit: m M



the photorealistic images are to be considered as reference images



Article Description

Industrial duct, 60x60x2000 mm, without cover, steel, pre-galvanised according to DIN EN 10346

Additional Price Information

Article group	N16
quantity unit	m

Technical Datasheet

Cable protection duct

LI 60.060

the photorealistic images are to be considered as reference images

Weight

Weight per quantity unit	992 g / m
Weight in kg per 100	99 kg / 100m

Physical Article Dimensions

Height	60.00 mm
Width	60.00 mm
Depth/length	2000 mm

Packing Dimension

2 meters = 1 piece		✓ VP1-smallest packaging unit (PU) ✓ VP1-preferred PU			
Lenght	2000 mm	Width	60.00 mm	Height	60.00 mm
Gross weight	1,98 kg	Volume	0,007 m³		
Min. quantity	2.00 m	Max. Quantity	2.00 m		
728 meters = 1 rack					
Lenght	2000 mm	Width	1162 mm	Height	1120 mm
Gross weight	820 kg	Volume	2,603 m³		
Min. Quantity	728.00 m	Max. Quantity	728.00 m		

Tender Text

Industrial duct, duct bottom part with staggered bottom and side perforations as well as additionally installed bottom and side outlets for cable and line bushings, without cover, accessories for equipotential bonding, two universal connectors LIV 60 per joint, must be ordered separately.

VDE certified!

Dimensions (approx. dimensions) H x W : 60 x 60 mm Floor outlets : 30 x 65 mm
Floor outlet

distance : 245 mm Side outlets : 20 x 65 mm Side outlet distance : 245 mm

Delivery length L : 2000 mm

Usable cross section : 3182 mm²

Material : Steel, pre-galvanised acc. to DIN EN 10346

NIEDAX Model No. : LI 60.060

EP Material_____ EP Wage_____

Unit price/meter

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059

Technical Datasheet

Cable protection duct

LI 60.060

the photorealistic images are to be considered as reference images

Related items

Cover

Model No.	Description
LD 60	Cable protection duct cover, 60x2000 mm, steel, pre-galvanised according to DIN EN 10346

Barrier strip

Model No.	Description
RW 60	Barrier strip, 55x3000 mm, t=0,75 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories
TPH 60	Barrier profile holder, channel depth 59 mm, steel, pre-galvanised according to DIN EN 10346
TPS 50	Barrier strip, height 11 mm, depth 50 mm, length 1996 mm, steel, pre-galvanised according to DIN EN 10346

Connector

Model No.	Description
LIV 60	Universal-splice plate, asymmetrical, steel, pre-galvanised according to DIN EN 10346, incl. accessories