



Elbow 90°

with unperforated side profiles, but with connector perforations

KLMUB 40.900 F

EAN Code: 4013339082421
 Smallest packaging unit:1 pc.

the photorealistic images are to be considered as reference images



Article Description

Elbow 90°, 40x900 mm, t=5,0 mm, steel, hot dip galvanised DIN EN ISO 1461

Excl. Accessories

exclusive bolting Please order the necessary fastening accessories separately: FLM 8X25 F

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	9,848 kg / pcs.
Weight in kg per 100	985 kg / 100pcs.

Technical Datasheet

Cable Ladder System

KLMUB 40.900 F

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	40.00 mm
Width	1360 mm
Depth/length	1360 mm

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	1360 mm	Width	1360 mm	Height	40.00 mm
Gross weight	9,85 kg	Volume	0,074 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

Elbow 90°, for marine cable ladders, with unperforated side rails but with connecting perforation for connection and welded-in, trapezoidal, perforated rungs, for creating 90° horizontally angled cable ladder run. Please order fastening accessories for the connection separately.

Used for : Marine cable ladder/vertical cable ladder KLMUL 40...

Dimensions (approx. dimensions)

Height H x width W (inside) : 40 x 900 mm

Material thickness t : 5 mm

Inside radius R : 300 mm

Material : Steel, hot-dip galvanised acc. to DIN EN ISO 1461

NIEDAX Model no. : KLMUB 40.900 F

EP Material_____ EP Wage_____

Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059