

Elbow 90°, small



made of oval, closed tubular profile bars and welded, closed, oval rungs

KROBK 60.425 F

EAN Code: 4013339849062

Smallest packaging unit: 1 pc.

the photorealistic images are to be considered as reference images



Article Description

Elbow 90°, small, 60x400 mm, with closed, oval rungs, steel, hot dip galvanised DIN EN ISO 1461

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	4,148 kg / pcs.
Weight in kg per 100	415 kg / 100pcs.

Physical Article Dimensions

Height	60.00 mm
Width	850 mm
Depth/length	850 mm

Technical Datasheet

Cable Ladder System

KROBK 60.425 F

the photorealistic images are to be considered as reference images

Packing Dimension

1 piece = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	850 mm	Width	850 mm	Height	60.00 mm
Gross weight	4,15 kg	Volume	0,043 m³		
Min. quantity	1.00 pcs.	Max. Quantity	1.00 pcs.		

Tender Text

Elbow 90°, small, side beams made of hollow sections, with welded-in, closed, oval rungs, for creating horizontal 90° elbows. Please order splice plate KRLV 60 F separately. for Allround cable ladder : KRC...

Dimensions (approx. dimensions) H x W : 60 x 400 mm Outer dimensions : 450 mm + B

Inner beam radius R : 300 mm

Material : Steel, hot-dip galvanised acc. to DIN EN ISO 1461

NIEDAX Model No. : KROBK 60.425 F

EP Material_____ EP Wage_____

Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Federal State of Origin	RP
Customs tariff number	73089059

Related items

Connector

Model No.	Description
KRLV 60 F	Splice plate, steel, hot dip galvanised DIN EN ISO 1461