

Cable Ladder

rung spacing 300 mm, with continuously perforated side profiles, with riveted, upwardly open rungs made of C-profiles with 11 mm slot width

KL 100.503/3




EAN Code: 4013339014873

Smallest packaging unit:3 m

quantity unit:m M



the photorealistic images are to be considered as reference images



Article Description

Cable ladder, 100x500x3000 mm, t=1,5 mm, perforated, steel, pre-galvanised according to DIN EN 10346

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	4,102 kg / m
Weight in kg per 100	410 kg / 100m

Technical Datasheet

Cable Ladder System

KL 100.503/3

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	100.00 mm
Width	500 mm
Depth/length	3000 mm

Packing Dimension

3 meters = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	3000 mm	Width	500 mm	Height	100.00 mm
Gross weight	12 kg	Volume	0,150 m³		
Min. quantity	3.00 m	Max. Quantity	3.00 m		

Tender Text

Cable ladder acc. to DIN EN 61537, with continuously perforated and profiled side rails, with riveted rungs made of C-profiles with 11 mm slot width.
Corresponding U-clamps: BA... and BAK...
Dimensions (approx. dimensions)
Height H x width W : 100 x 500 mm
Material thickness side rail : 1.5 mm
Rung distance : 300 mm
Side rail perforation : 9 x 15 mm
Center distance : 25 mm
Base perforation : Ø 8.5 and Ø 5.4 mm
Center distance : 100 mm and 50 mm
Delivery length L : 3000 mm
Transport length : 3000 mm + W
Usable cross-section : 41550 mm²
Material : Steel, pre-galvanised acc. to DIN EN 10346
NIEDAX Model No.: KL 100.503/3
EP Material_____ EP Wage_____
Unit price/meter

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Federal State of Origin	RP
Customs tariff number	73089059

Technical Datasheet

Cable Ladder System

KL 100.503/3

the photorealistic images are to be considered as reference images

Related items

Cover

Model No.	Description
RD 500	Cover for cable tray/-ladder, with joint strip, 502x3000 mm, steel, pre-galvanised according to DIN EN 10346
RDRS 9	Turning bolt with locking nut acc. to DIN EN ISO 10511, steel, pre-galvanised according to DIN EN 10346, incl. accessories
RDV 500	Cover for cable tray/-ladder, with joint strip, 502x3000 mm, steel, pre-galvanised according to DIN EN 10346

Barrier strip

Model No.	Description
KLWC 11	Barrier strip fastening clamp, for 11 mm slot width, steel, pre-galvanised according to DIN EN 10346, incl. accessories
RW 85	Barrier strip, 80x3000 mm, t=0,9 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories

Connector

Model No.	Description
KSV 100 S	Splice plate for cable ladder, height 100 mm, steel, pre-galvanised according to DIN EN 10346, incl. accessories