

Cable Ladder

rung spacing 300 mm, with continuously perforated side profiles, with riveted, upwardly open rungs made of C-profiles with 11 mm slot width

KL 60.403/3 E3




EAN Code: 4013339341146

Smallest packaging unit: 3 m

quantity unit: m M



the photorealistic images are to be considered as reference images



Article Description

Cable ladder, 60x400x3000 mm, t=1,5 mm, perforated, stainless steel, material code: 1.4301, AISI 304

Additional Price Information

Article group	N13
quantity unit	m

Weight

Weight per quantity unit	2,981 kg / m
Weight in kg per 100	298 kg / 100m

Technical Datasheet

Cable Ladder System

KL 60.403/3 E3

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	60.00 mm
Width	400 mm
Depth/length	3000 mm

Packing Dimension

3 meters = 1 piece		✓ VP1-smallest packaging unit (PU)			
Lenght	3000 mm	Width	400 mm	Height	60.00 mm
Gross weight	8,94 kg	Volume	0,072 m ³		
Min. quantity	3.00 m	Max. Quantity	3.00 m		

Tender Text

Cable ladder acc. to DIN EN 61537, with continuously perforated and profiled side rails, with riveted rungs made of C-profiles with 11 mm slot width.
Corresponding U-clamps: BA...
Dimensions (approx. dimensions)
Height H x width W : 60 x 400 mm
Material thickness side rail : 1.5 mm
Rung distance : 300 mm
Side rail perforation : 9 x 15 mm
Center distance : 25 mm
Base perforation : Ø 8.5 and Ø 5.4 mm
Center distance : 100 mm and 50 mm
Delivery length L : 3000 mm
Transport length : 3000 mm + W
Usable cross-section : 17200 mm²
Material : stainless steel, material no. 1.4301, AISI 304
NIEDAX Model No. : KL 60.403/3 E3
EP Material_____ EP Wage_____
Unit price/meter

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Federal State of Origin	RP
Customs tariff number	73089059

Technical Datasheet

Cable Ladder System

KL 60.403/3 E3

the photorealistic images are to be considered as reference images

Related items

Cover

Model No.	Description
RD 400 E3	Cover for cable tray/-ladder, with joint strip, 402x3000 mm, stainless steel, material code: 1.4301, AISI 304
RDRS 9 E3	Turning bolt with locking nut acc. to DIN EN ISO 10511, stainless steel, material code: 1.4301, AISI 304, incl. accessories
RDV 400 E3	Cover for cable tray/-ladder, with joint strip, 402x3000 mm, stainless steel, material code: 1.4301, AISI 304

Barrier strip

Model No.	Description
KLWC 11 E3	Barrier strip fastening clamp, for 11 mm slot width, stainless steel, material code: 1.4301, AISI 304, incl. accessories
RW 35 E3	Barrier strip, 30x3000 mm, t=0,8 mm, stainless steel, material code: 1.4301, AISI 304, incl. accessories

Connector

Model No.	Description
KSV 60 E3	Splice plate for cable ladder, height 60 mm, stainless steel, mat. code: 1.4301, AISI 304, washed,incl. accessories