


Splice Plate

KSV 60/320 S

EAN Code: 4013339059669
 Smallest packaging unit:20 pcs.

the photorealistic images are to be considered as reference images



Article Description

Splice plate for cable ladder, 60x320mm, steel, pre-galvanised according to DIN EN 10346

Incl. accessories

4 FLM 8X13 F

Additional Price Information

Article group	N13
quantity unit	pcs.

Weight

Weight per quantity unit	464 g / pcs.
Weight in kg per 100	46 kg / 100pcs.

Technical Datasheet

Cable Ladder System

KSV 60/320 S

the photorealistic images are to be considered as reference images

Physical Article Dimensions

Height	64.00 mm
Width	15.00 mm
Depth/length	320 mm

Packing Dimension

20 pieces = 1 carton		✓ VP1-smallest packaging unit (PU)		✓ VP1-preferred PU	
Lenght	350 mm	Width	180.00 mm	Height	110.00 mm
Gross weight	9,59 kg	Volume	0,007 m³		
Min. quantity	20.00 pcs.	Max. Quantity	20.00 pcs.		

480 pieces = 1					
Lenght	750 mm	Width	750 mm	Height	730 mm
Gross weight	270 kg	Volume	0,411 m³		
Min. Quantity	480.00 pcs.	Max. Quantity	480.00 pcs.		

Tender Text

Splice plate, to create a positive, longitudinally aligned connection, including proportional fastening accessories in hot-dip galvanised. The equipotential bonding is achieved by screwing it to the cable ladder and fitting beams. Can be used for : cable ladders, their fittings and vertical cable ladders with an edge height of 60 mm

Requirement : 2 pieces per joint Dimensions (approx. dimensions) H x L : 60 x 320 mm

Material : steel, pre- galvanised acc. to DIN EN 10346

NIEDAX Model No. : KSV 60/320 S

EP Material_____ EP Wage_____

Unit price/piece

Safety & Environment

REACH Date	25.06.2025
REACH Info	Conformable
RoHS Info	Conformable

Origin & International Trade

Country of origin	DE
Customs tariff number	73089059